



## VM FOOTWEAR BRAND STRENGTHENED ITS POSITION IN THE OCCUPATIONAL SHOE MARKET AND DEFENDED THE PRESTIGIOUS CZECH BUSINESS SUPERBRANDS TITLE FOR THE FIFTH TIME IN A ROW!

Superbrands is the most respected independent global authority in the field of evaluation and branding. The title of Superbrands is a sign of a special position and recognition of the excellent brand position in the local market. The Superbrands seal will receive brands with an outstanding reputation - customers connect significant values and personal relationships. Since its inception in the UK, the project has gained worldwide recognition, and today the Superbrands Award is recognized as a special award which, on the basis of unified criteria and methods, identifies the best of the best brands in nearly 90 states on five continents every year.

### WHO GETS THE TITLE SUPERBRANDS

The award of the Superbrands title for the given year is preceded by a multi-round tender. Individual brands can not be signed into the Superbrands program. The nomination is based on the database of all registered trademarks, which is released for this purpose by the Industrial Property Office. Bisnode company, the world's leading provider of business information, will create a list of nominated candidates based on business data and results. The next step is consumer research, one of the most important elements of the selection process, in which GfK Czech Republic agency, on the basis of connections and popularity, narrows the selection to the list of semifinalists. The final word for Superbrands title in the given year is the committee of the Brand Council. At the end of the rating process, consumers receive valuation of Superbrands, and business brands are awarded by the Business Superbrands title.

### SUPERBRANDS PROGRAM CZECH REPUBLIC

Superbrands has resumed its operations in the Czech Republic in 2013. Since 2014, brands have been evaluated not only in the consumer, but also in the area of business or industrial (B2B) brands. While the first is publicly known and consumers are meeting them every day in the retail or service sector, business brands are important players in the specialized branch of industry, agriculture and commerce. Consumer and business Superbrands of the given year represent the absolute best between competitors. With Superbrands title we express our admiration and sincerely honor its results in the field of building a successful brand. The most important goal of Superbrands organization is not only to give away the most successful branding brands, but also to bring to the attention of consumers and the professional public the extremely strong brands operating on the Czech market and to present examples of good follow-up for market participants who would like to develop and inspire from the best. For this purpose, Superbrands organization arranges annually a joint PR and media program for award-winning brands, to which only the Superbrands and Business Superbrands of the given year are invited.





## Basic CATEGORIES

## CLASSIFICATION OF THE FOOTWEAR ACCORDING TO THE LEVEL OF PROTECTION

## CATEGORY DESIGNATION

EN ISO 20347: 2012	occupational shoes	0B	01	02	03
EN ISO 20345: 2011	safety shoes	SB	S1	S2	S3

## Symbol RISKS COVERED

	basic requirements	X	X	X	X
	closed heel area	0	X	X	X
<b>E</b>	energy absorption in the heel area	0	X	X	X
<b>A</b>	antistatic properties	0	X	X	X
<b>WRU</b>	resistance of the upper of the shoe to penetration and absorption of water	0	0	X	X
<b>P</b>	puncture protection of the bottom of the shoe	0	0	0	X
	outsole with pattern	0	0	0	X
<b>CI</b>	insulation of the outsole against cold	0	0	0	0
<b>HI</b>	insulation of the outsole against heat	0	0	0	0
<b>HRO</b>	resistance of the outsole against contact heat	0	0	0	0
<b>WR</b>	durability of the whole shoe against water penetration	0	0	0	0
<b>FO</b>	resistance of the outsole against fuel oils /occupational shoes only/	0	0	0	0
<b>M</b>	instep protection /safety shoes only/	0	0	0	0
<b>SRA</b>		X	X	X	X
<b>SRB</b>	antislip resistance	X	X	X	X
<b>SRC</b>		X	X	X	X

## Size CHART

EU - EUROPEAN NUMBERING	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52												
MM (MONDO POINT)	195	200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320	325	330	335					
UK - ENGLISH NUMBERING	12,5	0	0,5	1	1,5	2	2,5	3	3,5	4	4,5	5	5,5	6	6,5	7	7,5	8	8,5	9	9,5	10	10,5	11	11,5	12	12,5	13	13,5	14	14,5	15	15,5	16
US - AMERICAN NUMBERING		1	1,5	2	2,5	3	3,5	4	4,5	5	5,5	6	6,5	7	7,5	8	8,5	9	9,5	10	10,5	11	11,5	12	12,5	13	13,5	14	14,5	15	15,5	16	16,5	17

## PICTOGRAMS



energy absorption  
in the heel area



outsole resistant to fuels  
oils /for occupational  
and safety shoes/



slip  
resistance



antistatic  
properties



protection against impact  
to 200 J and a pressure  
of 15 kN



protection of the footwear  
against punctures  
up to 1100 N



shoe upper resistance  
against penetration  
and water absorption



instep protection  
/for safety shoes only/



ESD antistatic  
properties



cold  
resistance



upper resistance  
against chain saw  
cutting



outsole resistant to  
contact heat  
up to 300°C





### MICROFIBRE

Upper HIGH-TECH material composed of microfibers, reaching the appearance, breathability, water resistance and parameters of the natural leather. Shoes can be washed at 40°C.



### SPACE COMFORT

The optimal width of shoes is guarantee the required comfort.



### HARDHEEL STRUCTURED

Modern solutions of the heel shoe part, which ensures maximal stabilization of the foot while walking and standing.



### FORCED CIRCULATION

Exhaust ventilation system combined with lining with absorbent capability. These shoes are "breathing" and provide maximum comfort.



### ANATOMIC AIR COMFORT

Special insole with gel insert in the heel shock absorbing (absorbs energy) while walking - bamboo fiber ensures extraction of water vapor and optimal climate inside the shoe.



### SOLES BY MICHELIN®

The outsoles are equipped with a combination of specially designed rubber compounds and are inspired by unique technical design of world famous brands Michelin® tires.

VM® | SYSTEMS





### METATARSAL

Special protection system of the vamp, designated for the area of smelters, foundries, etc.



ALWAYS A STEP AHEAD

BOA®

### BOA® Fit System

Patented „BOA® Fit System“ is reinventing how newly tight up the shoes. BOA® proprietary closure system of steel lace, nylon guides and a mechanical reel was designed to address the long list of deficiencies found in traditional closures.



### FREE-TEX® MEMBRANE

The membrane, as special sandwich of three vapor-permeable and a waterproof layers, together with innerlining and leather shoe uppers a perfect solution for optimum climate inside the shoe. Provides thermal-insulation, breathability and water resistance.



### ANTI-CUT

Special inner lining, 100% KEVLAR in total weight of 650g/m2. With several layers it provides resistance against chain saw.



### ANATOMIC DRY SOLE

Anatomic, comfortable and shaped insole with excellent water absorption and dries quickly.



### NON METALIC

Shoes without any metal components suitable for area that require it.





# Job & Walk



**2 X**  
ABOVE THE  
STANDARD

**LINING FREE-TEX®**  
WATER VAPOR  
PERMEABILITY

**3 X**  
ABOVE THE  
STANDARD

**LINING FREE-TEX®**  
WATER PERMEABILITY  
COEFFICIENT

**6 X**  
ABOVE THE  
STANDARD

**UPPER SOFTSHELL**  
WATER PERMEABILITY  
COEFFICIENT

**3 X**  
ABOVE THE  
STANDARD

**INNER INSOLE**  
WATER  
ABSORPTION

The footwear in the **Job & Walk** category are suitable for light outdoor use, indoor, unpretentious work environment. (drivers, managerial positions, logistics, management, rest, leisure, outdoor activities.)

In this category we offer mainly certified work, safety and employee footwear in timeless sports and outdoor design. We bring part of the collection in this category with the unique **Michelin® Technical Soles** and also with the unique, patented **BOA® Fit System**.





SOLES  
BY



#### SOLES BY MICHELIN®

The outsoles are equipped with a combination of specially designed rubber compounds and are inspired by unique technical design of world famous brands Michelin® tires.



#### BOA FIT® SYSTEM

Unique system of closing shoes.



#### FORCED CIRCULATION

Exhaust ventilation system combined with lining with absorbent capability. These shoes are "breathing" and provide maximum comfort.



#### ANATOMIC AIR COMFORT

Special insole with gel insert in the heel shock absorbing (absorbs energy) while walking - bamboo fiber ensures extraction of water vapor and optimal climate inside the shoe.



#### ANATOMIC DRY SOLE

Anatomically shaped insole with excellent absorbency and dryness.



#### SPACE COMFORT

Optimized ergonomics and shoe width.



#### ABRASION-RESISTANT

#### PUTEK FABRIC

High-strength polyamide fabric PUTEK.



#### MICROFIBRE

Upper HIGH-TECH material composed of microfibers, reaching the appearance, breathability, water resistance and parameters of the natural leather.



#### FREE-TEX® MEMBRANE

Vapor-permeable, water-resistant membrane.



#### SOFTSHELL

Textile functional material, ensuring water resistance



#### GLOBAL RECYCLING STANDARD

Standard recycled fibers.





OCCUPATIONAL SANDAL - FULL GRAIN LEATHER



**LINZ**

**3995**



**ORDER NO.** 3995-OB  
**VERSION** OB E SR - without toe cap  
**SIZE** 36 - 41  
**STANDARD** EN ISO 20347:2012  
**UPPER** cowhide leather in a thickness of 1,6 - 1,8 mm

**LINING** without lining  
**INNER INSOLE** anatomically shaped PHYLON  
**OUTSOLE** EVA/RUBBER - glued construction







LOW CUT SAFETY SHOES - TEXTILE

## NEBRASKA

4760

ORDER NO.	4760-S1P	LINING	laminated breathable fabric MESH
VERSION	S1P SRA - with composite toe cap and kevlar midsole	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	EVA/RUBBER - glued construction
STANDARD	EN ISO 20345:2011		
UPPER	breathable, abrasion-resistant knitted textile		



SPACE comfort



anatomic DRY SOLE

NOTE the footwear is not intended for a difficult working environment



LOW CUT SAFETY SHOES - TEXTILE

## GEORGIA

4735

ORDER NO.	4735-S1P	LINING	laminated breathable fabric MESH
VERSION	S1P SRA - with composite toe cap and kevlar midsole	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	EVA/RUBBER - glued construction
STANDARD	EN ISO 20345:2011		
UPPER	breathable, abrasion-resistant knitted textile		

NOTE the footwear is not intended for a difficult working environment



SPACE comfort



anatomic DRY SOLE



LOW CUT OCCUPATIONAL AND SAFETY SHOES  
LEATHER COMBINED WITH TEXTILE



## IOWA

4745

**ORDER NO.** 4745-01 | 4745-S1P

**VERSION 01** 01 FO SRA - without composite toe cap and kevlar midsole

**VERSION S1P** S1P SRA - with composite toe cap and kevlar midsole

**SIZE** 01: 37 - 48 | S1P: 36 - 48

**STANDARD** 01: EN ISO 20347:2011  
S1P: EN ISO 20345:2011

**UPPER** brushed cow suede leather **VELOUR** in a combination with textile in a thickness of 1,5 - 1,7 mm



**SPACE** comfort



**anatomic** DRY SOLE

**NOTE**

the footwear is not intended for a difficult working environment

**LINING** laminated breathable fabric **MESH**

**INNER INSOLE** **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic

**OUTSOLE** **EVA/RUBBER** - glued construction



LOW CUT SAFETY SHOES - LEATHER COMBINED WITH TEXTILE



## MISSISSIPPI

4755

**ORDER NO.** 4755-S1P

**VERSION** S1P SRA - with composite toe cap and kevlar midsole

**SIZE** 36 - 48

**STANDARD** EN ISO 20345:2011

**UPPER** brushed cow suede leather **VELOUR** in a combination with textile in a thickness of 1,5 - 1,7 mm

**LINING** laminated breathable fabric **MESH**

**INNER INSOLE** **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic

**OUTSOLE** **EVA/RUBBER** - glued construction

**NOTE**

the footwear is not intended for a difficult working environment



**SPACE** comfort



**anatomic** DRY SOLE







LOW CUT OCCUPATIONAL AND SAFETY SHOES - FULL GRAIN LEATHER

## TENERIFE

4795

ORDER NO. 4795-01 | 4795-S1P

VERSION 01 01 FO SRA - without composite toe cap and kevlar midsole

VERSION S1P S1P SRA - with composite toe cap and kevlar midsole

SIZE 01: 37 - 48 | S1P: 39 - 48

STANDARD 01: EN ISO 20347:2011  
S1P: EN ISO 20345:2011

UPPER synthetic, brushed EKO VELOUR material, abrasion resistant

LINING laminated breathable fabric MESH

INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic

OUTSOLE EVA/RUBBER - glued construction



SPACE comfort

FORCED CIRCULATION

anatomic DRY SOLE

NOTE

the footwear is not intended for a difficult working environment

RECYCLED  
PLASTIC  
BOTTLE  
FABRIC

LOW CUT SAFETY SHOES - TEXTILE, GRS CE

## LA PALMA

4775

ORDER NO. 4775-S1P

VERSION S1P SRA - with composite toe cap and kevlar midsole

SIZE 39 - 48

STANDARD EN ISO 20345:2011  
GRS CERTIFICATION

UPPER breathable, abrasion-resistant knitted textile, RECYCLED

LINING laminated breathable fabric MESH

INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic

OUTSOLE EVA/RUBBER - glued construction

NOTE

the footwear is not intended for a difficult working environment



SPACE comfort

FORCED CIRCULATION

anatomic DRY SOLE





LOW CUT SAFETY SHOES - TEXTILE, NON METALLIC, GRS CE



## PANAMA

4545

ORDER NO.	4545-S1P	LINING	laminated breathable fabric MESH
VERSION	S1P SRA - with composite toe cap and kevlar midsole, <b>NON METALLIC</b>	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	39 - 48	OUTSOLE	EVA/RUBBER - glued construction
STANDARD	EN ISO 20345:2011 GRS CERTIFICATION		
UPPER	breathable, abrasion-resistant knitted textile, <b>RECYCLED</b>		



SPACE comfort



anatomic DRY SOLE



NOTE

the footwear is not intended for a difficult working environment

NON METALLIC



LOW CUT SAFETY SHOES - TEXTILE, NON METALLIC, GRS CE



## MONACO

4555

ORDER NO.	4555-S1P	LINING	laminated breathable fabric MESH
VERSION	S1P SRA - with composite toe cap and kevlar midsole, <b>NON METALLIC</b>	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	39 - 48	OUTSOLE	EVA/RUBBER - glued construction
STANDARD	EN ISO 20345:2011 GRS CERTIFICATION		
UPPER	breathable, abrasion-resistant knitted textile, <b>RECYCLED</b>		

NOTE

the footwear is not intended for a difficult working environment



SPACE comfort



anatomic DRY SOLE

NON METALLIC





LOW CUT SAFETY SHOES  
SOFTSHELL, NON METALLIC, GRS CE



## MALLORCA

4785

ORDER NO.	4785-S1P	LINING	laminated breathable fabric MESH
VERSION	S1P SRA - with composite toe cap and kevlar midsole, NON METALLIC	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	39 - 48	OUTSOLE	EVA/RUBBER - glued construction
STANDARD	EN ISO 20345:2011 GRS CERTIFICATION		
UPPER	technologically advanced material SOFTSHELL, RECYCLED		



SPACE comfort



anatomic DRY SOLE



NOTE the footwear is not intended for a difficult working environment

NON METALLIC



JOB & WALK



LOW CUT SAFETY SHOES  
SOFTSHELL, GRS CE



## BRISBANE

4215

ORDER NO.	4215-SP	LINING	laminated breathable fabric MESH
VERSION	S1 SRA - with composite toe cap	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	39 - 48	OUTSOLE	EVA/RUBBER - glued construction
STANDARD	EN ISO 20345:2011 GRS CERTIFICATION		
UPPER	technologically advanced material SOFTSHELL, RECYCLED		



SPACE comfort



anatomic DRY SOLE





LOW CUT SAFETY AND OUTDOOR SHOES  
SYNTHETIC WITH CPU PRINT - WITH BOA® FIT SYSTEM



## PHILADELPHIA

4355

ORDER NO.	4355-S1P   4355-60	UPPER	breathable, abrasion-resistant textile with <b>CPU</b> printing
VERSION S1P	S1P SRA - with composite toe cap and kevlar midsole, with <b>Boa® Fit System</b>	LINING	laminated breathable fabric <b>MESH</b>
VERSION 60	outdoor, with <b>Boa® Fit System</b>	INNER INSOLE	anatomically shaped from material <b>EVA</b> with a high absorbency, antistatic
SIZE	38 - 47	OUTSOLE	<b>EVA/RUBBER</b> - resistant to fuel oils, antistatic, antislip, glued construction
STANDARD S1P	EN ISO 20345:2011		
USABILITY 60	shoes suitable for daily wear and light outdoor activities		



### NOTE

the upper of the shoe must not come into contact with an aggressive acid or base!



LOW CUT SAFETY SHOES - SYNTHETIC WITH CPU PRINT



## NASHVILLE

4345

ORDER NO.	4345-S1	LINING	laminated breathable fabric <b>MESH</b>
VERSION	S1 SRA - with composite toe cap	INNER INSOLE	anatomically shaped from material <b>EVA</b> with a high absorbency, antistatic
SIZE	39 - 47	OUTSOLE	<b>EVA/RUBBER</b> - resistant to fuel oils, antistatic, antislip, glued construction
STANDARD	EN ISO 20345:2011		
UPPER	breathable, abrasion-resistant textile with <b>CPU</b> printing		



### NOTE

the upper of the shoe must not come into contact with an aggressive acid or base!



LOW CUT SAFETY SHOES  
TEXTILE WITH TPU PRINT - WITH BOA® FIT SYSTEM



## LOUISIANA

6335

<b>ORDER NO.</b>	6335-S1P	<b>LINING</b>	laminated breathable fabric <b>MESH</b>
<b>VERSION</b>	S1P SRC - with composite toe cap and kevlar midsole <b>BOA® Fit System</b>	<b>INNER INSOLE</b>	<b>HI-POLY</b> - anatomically shaped, lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
<b>SIZE</b>	39 - 47	<b>OUTSOLE</b>	<b>EVA/RUBBER</b> - resistant to fuel oils, antistatic, antislip, glued construction
<b>STANDARD</b>	EN ISO 20345:2011		
<b>UPPER</b>	breathable abrasion resistant textile with <b>TPU</b> print		



**NOTE** the upper of the shoe must not come into contact with an aggressive acid or base!



LOW CUT SAFETY SHOES - TEXTILE



## MONTGOMERY

6345

<b>ORDER NO.</b>	6345-S1P	<b>LINING</b>	laminated breathable fabric <b>MESH</b>
<b>VERSION</b>	S1P SRC - with composite toe cap and kevlar midsole	<b>INNER INSOLE</b>	<b>HI-POLY</b> - anatomically shaped, lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
<b>SIZE</b>	39 - 47	<b>OUTSOLE</b>	<b>EVA/RUBBER</b> - resistant to fuel oils, antistatic, antislip, glued construction
<b>STANDARD</b>	EN ISO 20345:2011		
<b>UPPER</b>	abrasion resistant, breathable textile		





LOW CUT SAFETY SHOES - SOFTSHELL  
WITH BOA® FIT SYSTEM, WITH MICHELIN® OUTSOLE



## CINCINNATI

4845

ORDER NO.	4845-S1P	LINING	laminated breathable fabric MESH
VERSION	S1P SRC - with composite toe cap and kevlar midsole, BOA® Fit System	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	39 - 47	OUTSOLE	MICHELIN® EVA/RUBBER - resistant to fuel oils, antislip, antistatic
STANDARD	EN ISO 20345:2011		
UPPER	technologically advanced SOFTSHELL material		



LOW CUT SAFETY SHOES - SOFTSHELL  
WITH MICHELIN® OUTSOLE



## OHIO

4855

ORDER NO.	4855-S1P	LINING	laminated breathable fabric MESH
VERSION	S1P SRC - with composite toe cap and kevlar midsole	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	39 - 47	OUTSOLE	MICHELIN® EVA/RUBBER - resistant to fuel oils, antislip, antistatic
STANDARD	EN ISO 20345:2011		
UPPER	technologically advanced SOFTSHELL material		





LOW CUT OUTDOOR SHOES - SOFTSHELL  
WITH MEMBRANE FREE-TEX®, WITH MICHELIN® OUTSOLE



## FLORIDA

4865

ORDER NO.	4865-60	LINING	breathable thermo-insulation <b>MEMBRANE FREE-TEX®</b>
VERSION	black colour, <b>MEMBRANE FREE-TEX®</b>	INNER INSOLE	<b>HI-POLY</b> - anatomically shaped, lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
SIZE	39 - 47	OUTSOLE	<b>MICHELIN® EVA/RUBBER</b> - glued construction
USABILITY	shoes suitable for daily wear and outdoor activities		
UPPER	technologically advanced <b>SOFTSHELL</b> material		



LOW CUT SAFETY SHOES  
POLYAMIDE FABRIC PUTEK



## MINNESOTA

4875

ORDER NO.	4875-53	LINING	laminated breathable fabric <b>MESH</b>
VERSION	<b>S3 SRA</b> - with composite toe cap and kevlar midsole	INNER INSOLE	<b>HI-POLY</b> - anatomically shaped, lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
SIZE	37 - 47	OUTSOLE	<b>EVA/RUBBER</b> - resistant to fuel oils, antislip, antistatic, glued construction
STANDARD	EN ISO 20345:2011		
UPPER	polyamide abrasion resistant fabric <b>PUTEK</b>		





LOW CUT OCCUPATIONAL SHOES - FULL GRAIN LEATHER  
WITH MEMBRANE FREE-TEX®, WITH MICHELIN® OUTSOLE



## VIRGINIA

4375

ORDER NO.	4375-02	LINING	breathable thermo-insulation <b>MEMBRANE FREE-TEX®</b>
VERSION	02 FO SRC - without steel toe cap, hydrophobic, <b>MEMBRANE FREE-TEX®</b>	INNER INSOLE	<b>HI-POLY</b> - anatomically shaped, lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
SIZE	38 - 47	OUTSOLE	<b>MICHELIN® EVA/RUBBER</b> - resistant to fuel oils, antislip, antistatic, glued construction
STANDARD	EN ISO 20347:2012		
UPPER	cowhide leather <b>NUBUCK</b> in a thickness of 1,9 - 2,1 mm		



SPACE comfort



anatomic DRY SOLE



SOLES BY



### NOTE

color divergence of the material is not a fault | footwear is not designed for all-day workload!



ANKLE OCCUPATIONAL SHOES - FULL GRAIN LEATHER  
WITH MEMBRANE FREE-TEX®, WITH MICHELIN® OUTSOLE



## TEXAS

4360

ORDER NO.	4360-02	LINING	breathable thermo-insulation <b>MEMBRANE FREE-TEX®</b>
VERSION	02 FO SRC - without steel toe cap, hydrophobic, <b>MEMBRANE FREE-TEX®</b>	INNER INSOLE	<b>HI-POLY</b> - anatomically shaped, lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
SIZE	38 - 47	OUTSOLE	<b>MICHELIN® EVA/RUBBER</b> - resistant to fuel oils, antislip, antistatic, glued construction
STANDARD	EN ISO 20347:2012		
UPPER	cowhide leather <b>NUBUCK</b> in a thickness of 1,9 - 2,1 mm		



SPACE comfort



anatomic DRY SOLE



SOLES BY



### NOTE

color divergence of the material is not a fault | footwear is not designed for all-day workload!



LOW CUT OCCUPATIONAL SHOES - FULL GRAIN LEATHER  
WITH MEMBRANE FREE-TEX®, WITH MICHELIN® OUTSOLE



## OKLAHOMA

4385

ORDER NO.	4385-02	LINING	breathable thermo-insulation <b>MEMBRANE FREE-TEX®</b>
VERSION	02 FO SRC - without steel toe cap, hydrophobic, <b>MEMBRANE FREE-TEX®</b>	INNER INSOLE	<b>HI-POLY</b> - anatomically shaped, lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
SIZE	38 - 47	OUTSOLE	<b>MICHELIN® EVA/RUBBER</b> - resistant to fuel oils, antislip, antistatic, glued construction
STANDARD	EN ISO 20347:2012		
UPPER	cowhide leather <b>NUBUCK</b> in a thickness of 1,9 - 2,1 mm		



SPACE comfort



anatomic DRY SOLE



SOLES BY



### NOTE

color divergence of the material is not a fault | footwear is not designed for all-day workload!



ANKLE OCCUPATIONAL SHOES - FULL GRAIN LEATHER  
WITH MEMBRANE FREE-TEX®, WITH MICHELIN® OUTSOLE



## PITTSBURGH

4380

ORDER NO.	4380-02	LINING	breathable thermo-insulation <b>MEMBRANE FREE-TEX®</b>
VERSION	02 FO SRC - without steel toe cap, hydrophobic, <b>MEMBRANE FREE-TEX®</b>	INNER INSOLE	<b>HI-POLY</b> - anatomically shaped, lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
SIZE	38 - 47	OUTSOLE	<b>MICHELIN® EVA/RUBBER</b> - resistant to fuel oils, antislip, antistatic, glued construction
STANDARD	EN ISO 20347:2012		
UPPER	cowhide leather <b>NUBUCK</b> in a thickness of 1,9 - 2,1 mm		



SPACE comfort



anatomic DRY SOLE



SOLES BY



### NOTE

color divergence of the material is not a fault | footwear is not designed for all-day workload!



LOW CUT OCCUPATIONAL SHOES - FULL GRAIN LEATHER  
WITH MEMBRANE FREE-TEX®



## HAVANA

4315

ORDER NO.	4315-02	LINING	breathable thermo-insulation <b>MEMBRANE FREE-TEX®</b>
VERSION	OB E WRU SRA - without steel toe cap, hydrophobic, <b>FREE-TEX®</b>	INNER INSOLE	<b>HI-POLY</b> - anatomically shaped lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
SIZE	36 - 49	OUTSOLE	<b>EVA/RUBBER</b> - antislip, antistatic, glued construction
STANDARD	EN ISO 20347:2012		
UPPER	cowhide leather <b>NUBUCK</b> in a thickness of 1,9 - 2,1 mm		



**NOTE** color divergence of the material is not a fault | footwear is not designed for all-day workload!



ANKLE OCCUPATIONAL SHOES - FULL GRAIN LEATHER  
WITH MEMBRANE FREE-TEX®



## LA PAZ

4310

ORDER NO.	4310-02	LINING	breathable thermo-insulation <b>MEMBRANE FREE-TEX®</b>
VERSION	OB E WRU SRA - without steel toe cap, hydrophobic, <b>FREE-TEX®</b>	INNER INSOLE	<b>HI-POLY</b> - anatomically shaped lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
SIZE	36 - 49	OUTSOLE	<b>EVA/RUBBER</b> - antislip, antistatic, glued construction
STANDARD	EN ISO 20347:2012		
UPPER	cowhide leather <b>NUBUCK</b> in a thickness of 1,9 - 2,1 mm		

**NOTE** color divergence of the material is not a fault | footwear is not designed for all-day workload!





LOW CUT OCCUPATIONAL SHOES  
FULL GRAIN LEATHER WITH MEMBRANE FREE-TEX®



## LIMA

4115

ORDER NO.	4115-02	LINING	breathable thermo-insulation <b>MEMBRANE FREE-TEX®</b>
VERSION	OB E WRU SRA - without steel toe cap, hydrophobic, <b>FREE-TEX®</b>	INNER INSOLE	<b>HI-POLY</b> - anatomically shaped lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
SIZE	36 - 49	OUTSOLE	<b>EVA/RUBBER</b> - antislip, antistatic, glued construction
STANDARD	EN ISO 20347:2012		
UPPER	cowhide leather <b>NUBUCK</b> in a thickness of 1,9 - 2,1 mm		



**NOTE** footwear is not designed for all-day workload!



LOW CUT OCCUPATIONAL SHOES  
LEATHER COMBINED WITH TEXTILE



## BRASILIA

4415

ORDER NO.	4415-01	LINING	laminated breathable fabric <b>MESH</b>
VERSION	01 FO SRA - without steel toe cap	INNER INSOLE	<b>HI-POLY</b> - anatomically shaped lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
SIZE	36 - 49	OUTSOLE	<b>EVA/RUBBER</b> - resistant to fuel oils, antislip, antistatic, glued construction
STANDARD	EN ISO 20347:2012		
UPPER	brushed cow suede leather <b>VELOUR</b> in a thickness of 1,6 - 1,8 mm		



**NOTE** footwear is not designed for all-day workload!





ANKLE OCCUPATIONAL SHOES - FULL GRAIN LEATHER  
WITH MEMBRANE FREE-TEX®



## SANTIAGO

4170

ORDER NO.	4170-02	LINING	breathable thermo-insulation MEMBRANE FREE-TEX®
VERSION	OB E WRU SRA - without steel toe cap, hydrophobic, FREE-TEX®	INNER INSOLE	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	EVA/RUBBER - antislip, antistatic, glued construction
STANDARD	EN ISO 20347:2012		
UPPER	cowhide leather <b>NUBUCK</b> in a thickness of 1,9 - 2,1 mm		



**NOTE**

color divergence of the material is not a fault | footwear is not designed for all-day workload!



ANKLE OUTDOOR SHOES - FULL GRAIN LEATHER  
WITH MEMBRANE FREE-TEX®



## VILLACH

4150

ORDER NO.	4150-40	LINING	breathable thermo-insulation MEMBRANE FREE-TEX®
VERSION	brown colour, FREE-TEX®	INNER INSOLE	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	39 - 47	OUTSOLE	EVA/RUBBER glued construction
USABILITY	shoes suitable for daily wear and outdoor activities		
UPPER	cowhide leather <b>PULL-UP</b> in a thickness of 1,9 - 2,1 mm		

**NOTE**

color divergence of the material is not a fault





ANKLE OUTDOOR SHOES - TEXTILE WITH TPU PRINT  
WITH MEMBRANE FREE-TEX®, WITH MICHELIN® OUTSOLE



## LAS VEGAS

4880

ORDER NO.	4880-60	LINING	breathable thermo-insulation <b>MEMBRANE FREE-TEX®</b>
VERSION	black colour, <b>MEMBRANE FREE-TEX®</b>	INNER INSOLE	<b>HI-POLY</b> - anatomically shaped lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
SIZE	40 - 47	OUTSOLE	<b>MICHELIN®-EVA/RUBBER</b> - glued construction, antislip <b>ICE GRIP TECHNOLOGY</b>
USABILITY	shoes suitable for daily wear and light outdoor activities		
UPPER	abrasion resistant and waterproof textile with <b>TPU</b> print		



ANKLE OUTDOOR SHOES - FULL GRAIN LEATHER  
WITH MEMBRANE FREE-TEX®



## NEW BOSTON

4920

ORDER NO.	4920-08	LINING	breathable thermo-insulation <b>MEMBRANE FREE-TEX®</b>
VERSION	khaki colour, <b>FREE-TEX®</b>	INNER INSOLE	<b>HI-POLY</b> - anatomically shaped lightweight polyurethane foam coated with fabric <b>MESH</b> , antistatic
SIZE	36 - 48	OUTSOLE	<b>EVA/RUBBER</b> glued construction
USABILITY	shoes suitable for daily wear and outdoor activities		
UPPER	cowhide leather <b>NUBUCK</b> in a thickness of 1,9 - 2,1 mm		

NOTE color divergence of the material is not a fault





