



VM FOOTWEAR BRAND STRENGTHENED ITS POSITION IN THE OCCUPATIONAL SHOE MARKET AND DEFENDED THE PRESTIGIOUS CZECH BUSINESS SUPERBRANDS TITLE FOR THE FIFTH TIME IN A ROW!

Superbrands is the most respected independent global authority in the field of evaluation and branding. The title of Superbrands is a sign of a special position and recognition of the excellent brand position in the local market. The Superbrands seal will receive brands with an outstanding reputation - customers connect significant values and personal relationships. Since its inception in the UK, the project has gained worldwide recognition, and today the Superbrands Award is recognized as a special award which, on the basis of unified criteria and methods, identifies the best of the best brands in nearly 90 states on five continents every year.

WHO GETS THE TITLE SUPERBRANDS

The award of the Superbrands title for the given year is preceded by a multi-round tender. Individual brands can not be signed into the Superbrands program. The nomination is based on the database of all registered trademarks, which is released for this purpose by the Industrial Property Office. Bisnode company, the world's leading provider of business information, will create a list of nominated candidates based on business data and results. The next step is consumer research, one of the most important elements of the selection process, in which GfK Czech Republic agency, on the basis of connections and popularity, narrows the selection to the list of semifinalists. The final word for Superbrands title in the given year is the committee of the Brand Council. At the end of the rating process, consumers receive valuation of Superbrands, and business brands are awarded by the Business Superbrands title.

SUPERBRANDS PROGRAM CZECH REPUBLIC

Superbrands has resumed its operations in the Czech Republic in 2013. Since 2014, brands have been evaluated not only in the consumer, but also in the area of business or industrial (B2B) brands. While the first is publicly known and consumers are meeting them every day in the retail or service sector, business brands are important players in the specialized branch of industry, agriculture and commerce. Consumer and business Superbrands of the given year represent the absolute best between competitors. With Superbrands title we express our admiration and sincerely honor its results in the field of building a successful brand. The most important goal of Superbrands organization is not only to give away the most successful branding brands, but also to bring to the attention of consumers and the professional public the extremely strong brands operating on the Czech market and to present examples of good follow-up for market participants who would like to develop and inspire from the best. For this purpose, Superbrands organization arranges annually a joint PR and media program for award-winning brands, to which only the Superbrands and Business Superbrands of the given year are invited.



Basic CATEGORIES

CLASSIFICATION OF THE FOOTWEAR ACCORDING TO THE LEVEL OF PROTECTION

CATEGORY DESIGNATION

EN ISO 20347: 2012	occupational shoes	0B	01	02	03
EN ISO 20345: 2011	safety shoes	SB	S1	S2	S3

Symbol RISKS COVERED

	basic requirements	X	X	X	X
	closed heel area	0	X	X	X
E	energy absorption in the heel area	0	X	X	X
A	antistatic properties	0	X	X	X
WRU	resistance of the upper of the shoe to penetration and absorption of water	0	0	X	X
P	puncture protection of the bottom of the shoe	0	0	0	X
	outsole with pattern	0	0	0	X
CI	insulation of the outsole against cold	0	0	0	0
HI	insulation of the outsole against heat	0	0	0	0
HRO	resistance of the outsole against contact heat	0	0	0	0
WR	durability of the whole shoe against water penetration	0	0	0	0
FO	resistance of the outsole against fuel oils /occupational shoes only/	0	0	0	0
M	instep protection /safety shoes only/	0	0	0	0
SRA		X	X	X	X
SRB	antislip resistance	X	X	X	X
SRC		X	X	X	X

Size CHART

EU - EUROPEAN NUMBERING	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52												
MM (MONDO POINT)	195	200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320	325	330	335					
UK - ENGLISH NUMBERING	12,5	0	0,5	1	1,5	2	2,5	3	3,5	4	4,5	5	5,5	6	6,5	7	7,5	8	8,5	9	9,5	10	10,5	11	11,5	12	12,5	13	13,5	14	14,5	15	15,5	16
US - AMERICAN NUMBERING		1	1,5	2	2,5	3	3,5	4	4,5	5	5,5	6	6,5	7	7,5	8	8,5	9	9,5	10	10,5	11	11,5	12	12,5	13	13,5	14	14,5	15	15,5	16	16,5	17

PICTOGRAMS



energy absorption in the heel area



outsole resistant to fuels oils /for occupational and safety shoes/



slip resistance



antistatic properties



protection against impact to 200 J and a pressure of 15 kN



protection of the footwear against punctures up to 1100 N



shoe upper resistance against penetration and water absorption



instep protection /for safety shoes only/



ESD antistatic properties



cold resistance



upper resistance against chain saw cutting



outsole resistant to contact heat up to 300°C



MICROFIBRE

Upper HIGH-TECH material composed of microfibers, reaching the appearance, breathability, water resistance and parameters of the natural leather. Shoes can be washed at 40°C.



SPACE COMFORT

The optimal width of shoes is guarantee the required comfort.



HARDHEEL STRUCTURED

Modern solutions of the heel shoe part, which ensures maximal stabilization of the foot while walking and standing.



FORCED CIRCULATION

Exhaust ventilation system combined with lining with absorbent capability. These shoes are "breathing" and provide maximum comfort.



ANATOMIC AIR COMFORT

Special insole with gel insert in the heel shock absorbing (absorbs energy) while walking - bamboo fiber ensures extraction of water vapor and optimal climate inside the shoe.



SOLES BY MICHELIN®

The outsoles are equipped with a combination of specially designed rubber compounds and are inspired by unique technical design of world famous brands Michelin® tires.

VM® | SYSTEMS



METATARSAL

Special protection system of the vamp, designated for the area of smelters, foundries, etc.



ALWAYS A STEP AHEAD

BOA®

BOA® Fit System

Patented „BOA® Fit System" is reinventing how newly tight up the shoes. BOA® proprietary closure system of steel lace, nylon guides and a mechanical reel was designed to address the long list of deficiencies found in traditional closures.



FREE-TEX® MEMBRANE

The membrane, as special sandwich of three vapor-permeable and a waterproof layers, together with innerlining and leather shoe uppers a perfect solution for optimum climate inside the shoe. Provides thermal-insulation, breathability and water resistance.



ANTI-CUT

Special inner lining, 100% KEVLAR in total weight of 650g/m2. With several layers it provides resistance against chain saw.



ANATOMIC DRY SOLE

Anatomic, comfortable and shaped insole with excellent water absorption and dries quickly.



NON METALIC

Shoes without any metal components suitable for area that require it.



Strong & Safety

16X
ABOVE THE
STANDARD

UPPER PUTEK
ABRASION RESISTANCE

2X
ABOVE THE
STANDARD

UPPER PUTEK
STRENGTH

38X
ABOVE THE
STANDARD

UPPER PUTEK
WATER VAPOR PERMEABILITY

2X
ABOVE THE
STANDARD

UPPER NUBUCK
STRENGTH IN TEAR OF CHINK

3X
ABOVE THE
STANDARD

INNER INSOLE
WATER ABSORPTION

In the **Strong & Safety** category, we offer footwear that is suitable for indoor and outdoor use, for medium-heavy environments, industrial companies, logistics and transport, for various trades,


for outdoor operations and warehouses. We bring part of the collection in this category with unique **Michelin® Technical Soles** and also with the unique patented **BOA® Fit System**.

SOLES
BY



SOLES BY MICHELIN®

The outsoles are equipped with a combination of specially designed rubber compounds and are inspired by unique technical design of world famous brands Michelin® tires.



FREE-TEX® MEMBRANE

Vapor-permeable, water-resistant membrane.

anatomic DRY SOLE

ANATOMIC DRY SOLE

Anatomically shaped insole with excellent absorbency and dryness.

NON METALIC

NON METALIC

Shoes without any metal components suitable for area that require it.



FORCED CIRCULATION

Exhaust ventilation system combined with lining with absorbent capability. These shoes are "breathing" and provide maximum comfort.



SPACE COMFORT

Optimized ergonomics and shoe width.



HRO

The outsoles resistant to fuel oils and contact heat HRO up to 300 °C.

PU-TEK

ABRASION-RESISTANT PUTEK FABRIC

High-strength polyamide fabric PUTEK

SAFETY BOOTS - CHAIN SAW RESISTANT - FULL GRAIN LEATHER
WITH MEMBRANE FREE-TEX®, ANTICUT LEVEL 2



CURYCH

6650

ORDER NO.	6650-S3	LINING	breathable thermo-insulation MEMBRANE FREE-TEX® + 3M THINSULATE
VERSION	S3 HRO SRC CI ANTICUT LEVEL 2 - with composite toe cap and kevlar midsole, hydrophobic, anticut kevlar lining, kevlar sewing	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	39 - 47	OUTSOLE	EVA/RUBBER - glued construction, antistatic, antislip
STANDARD	EN ISO 20345:2011 EN ISO 17249		
UPPER	brushed cow suede leather VELOUR in a thickness of 2,0 - 2,2 mm		



SPACE comfort

FORCED CIRCULATION

anatomic

DRY SOLE ANTI-CUT



ANKLE OCCUPATIONAL SHOES
FULL GRAIN LEATHER - FARMER



DURANGO

2740

ORDER NO.	2740-01	LINING	CAMBRELLA fabric with absorbency
VERSION	01 FO SRC - without toe cap and midsole	INNER INSOLE	anatomically shaped with latex heel pad, coated with CAMBRELLA, antistatic
SIZE	37 - 47	OUTSOLE	PU/PU - resistant to fuel oils, antislip, antistatic, double density injection
STANDARD	EN ISO 20347:2012		
UPPER	cowhide leather NUBUCK in a thickness of 1,8 - 2,0 mm		



SPACE comfort

FORCED CIRCULATION

anatomic

DRY SOLE

ANKLE SAFETY SHOES
FULL GRAIN LEATHER WITH MEMBRANE FREE-TEX®



DORTMUND

2540

ORDER NO. 2540-S3

VERSION S3 HRO SRC - with composite toe cap and kevlar midsole, hydrophobic, **MEMBRANE FREE-TEX®**

SIZE 39 - 48

STANDARD EN ISO 20345:2011

UPPER cowhide leather **PULL-UP** in a thickness of 2,0 - 2,2 mm

LINING

breathable thermo-insulation
MEMBRANE FREE-TEX®

INNER
INSOLE

HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic

OUTSOLE

PU/RUBBER - up to 300°C, resistant to fuel oils, antislip, antistatic, double density injection



HARDHEEL
STRUCTURES

SPACE comfort

FORCED
CIRCULATION

anatomic
DRY SOLE

300°C
AAA HRO



ANKLE OCCUPATIONAL SHOES
FULL GRAIN LEATHER WITH MEMBRANE FREE-TEX®



STUTT GART

2550

ORDER NO. 2550-02

VERSION O2 FO HRO SRC - without composite toe cap and kevlar midsole, hydrophobic, **MEMBRANE FREE-TEX®**

SIZE 39 - 48

STANDARD EN ISO 20347:2012

UPPER cowhide leather **PULL-UP** in a thickness of 2,0 - 2,1 mm

LINING

breathable thermo-insulation
MEMBRANE FREE-TEX®

INNER
INSOLE

HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic

OUTSOLE

PU/RUBBER - up to 300°C, resistant to fuel oils, antislip, antistatic, double density injection



HARDHEEL
STRUCTURES

SPACE comfort

FORCED
CIRCULATION

anatomic
DRY SOLE

300°C
AAA HRO



ANKLE SAFETY SHOES
FULL GRAIN LEATHER, WITH MICHELIN® OUTSOLE



LOS ANGELES

6440

ORDER NO.	6440-S3	LINING	laminated breathable fabric MESH
VERSION	S3 SRC - with composite toe cap and kevlar midsole, hydrophobic	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	39 - 48	OUTSOLE	MICHELIN®-PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, antislip, antistatic
STANDARD	EN ISO 20345:2011		
UPPER	cowhide leather coated, brushed in a thickness of 1,8 - 2,0 mm		
NOTE	the upper of the shoe must not come into contact with an aggressive acid or base!		



ANKLE OCCUPATIONAL SHOES
WITH MEMBRANE FREE-TEX®, WITH MICHELIN® OUTSOLE,
NON METALLIC - FULL GRAIN LEATHER



ARKANSAS

6430

ORDER NO.	6430-S3	LINING	breathable thermo-insulation MEMBRANE FREE-TEX®
VERSION	S3 HRO SRC - with composite toe cap and kevlar midsole, hydrophobic, FREE-TEX®	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	39 - 48	OUTSOLE	MICHELIN®-PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, anti-slip, antistatic
STANDARD	EN ISO 20345:2011		
UPPER	cowhide leather NUBUCK in a thickness of 1,9 - 2,1 mm		



ANKLE SAFETY SHOES - FULL GRAIN LEATHER



MASKAT

5440

ORDER NO.	5440-S1P	LINING	laminated breathable fabric MESH
VERSION	S1P HRO SRC - with composite toe cap and kevlar midsole	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	36 - 48	OUTSOLE	PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	brushed cow suede leather, coated in a thickness of 1,8 - 2,0 mm		



SPACE comfort

FORCED CIRCULATION

anatomic DRY SOLE



NOTE the upper of the shoe must not come into contact with an aggressive acid or base!



STRONG & SAFETY

SAFETY BOOTS
FULL GRAIN LEATHER, WINTER DESIGN



EDINBURGH

5180

ORDER NO.	5180-S3	LINING	hair plush DELTA
VERSION	S3 CI SRC - with composite toe cap and kevlar midsole, hydrophobic, winter design	INNER INSOLE	anatomically shaped, coated with hair plush DELTA , antistatic
SIZE	39 - 48	OUTSOLE	PU/PU - resistant to fuel oils, antislip, antistatic, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	cowhide leather CRAZY HORSE in a thickness of 1,9 - 2,1 mm		



SPACE comfort

FORCED CIRCULATION

anatomic DRY SOLE

LOW CUT SAFETY SHOES - FULL GRAIN LEATHER



BRAGA

2685

ORDER NO. 2685-S3

VERSION S3 HRO SRC - with composite toe cap and kevlar midsole, hydrophobic

SIZE 39 - 48

STANDARD EN ISO 20345:2011

UPPER brushed cow suede leather VELOUR in a thickness of 1,7 - 1,9 mm

LINING

laminated breathable fabric MESH

INNER INSOLE

HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic

OUTSOLE

PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection



ANKLE SAFETY SHOES - FULL GRAIN LEATHER



PORTO

2680

ORDER NO. 2680-S3

VERSION S3 HRO SRC - with composite toe cap and kevlar midsole, hydrophobic

SIZE 39 - 48

STANDARD EN ISO 20345:2011

UPPER brushed cow suede leather VELOUR in a thickness of 1,7 - 1,9 mm

LINING

laminated breathable fabric MESH

INNER INSOLE

HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic

OUTSOLE

PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection



LOW CUT SAFETY SHOES
FULL GRAIN LEATHER



ASTANA

2765

ORDER NO.	2765-S3	LINING	laminated breathable fabric MESH
VERSION	S3 SRC - with composite toe cap and kevlar midsole, hydrophobic	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, antistatic, double density injection, antislip
STANDARD	EN ISO 20345:2011		
UPPER	cowhide leather NUBUCK in a thickness of 1,8 - 2,0 mm		



SPACE comfort



anatomic DRY SOLE

NOTE divergence of the material color shades is not a fault



ANKLE SAFETY SHOES
FULL GRAIN LEATHER



DAMASK

2760

ORDER NO.	2760-S3	LINING	laminated breathable fabric MESH
VERSION	S3 SRC - with composite toe cap and kevlar midsole, hydrophobic	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, antistatic, double density injection, antislip
STANDARD	EN ISO 20345:2011		
UPPER	cowhide leather NUBUCK in a thickness of 1,8 - 2,0 mm		



SPACE comfort



anatomic DRY SOLE

NOTE divergence of the material color shades is not a fault

LOW CUT SAFETY SHOES
FULL GRAIN LEATHER, NON METALLIC



MIAMI

5125

ORDER NO. 5125-S3

VERSION S3 SRC - with composite toe cap and kevlar midsole, hydrophobic, **NON METALLIC**

SIZE 36 - 48

STANDARD EN ISO 20345:2011

UPPER cowhide leather **NUBUCK** in a thickness of 1,8 - 2,0 mm

LINING laminated breathable fabric **MESH**

INNER INSOLE anatomically shaped from material **EVA** with a high absorbency, antistatic

OUTSOLE **PU/TPU - transparent** - resistant to fuel oils, antistatic, double density injection, antislip



ANKLE SAFETY SHOES
FULL GRAIN LEATHER, NON METALLIC



OXFORD

5130

ORDER NO. 5130-S3

VERSION S3 SRC - with composite toe cap and kevlar midsole, hydrophobic, **NON METALLIC**

SIZE 36 - 48

STANDARD EN ISO 20345:2011

UPPER cowhide leather **NUBUCK** in a thickness of 1,8 - 2,0 mm

LINING laminated breathable fabric **MESH**

INNER INSOLE anatomically shaped from material **EVA** with a high absorbency, antistatic

OUTSOLE **PU/TPU - transparent** - resistant to fuel oils, antistatic, double density injection, antislip



SAFETY SANDAL
FULL GRAIN LEATHER, NON METALLIC



KANSAS

5105

ORDER NO. 5105-S1P

VERSION S1P SRC - with composite toe cap and kevlar midsole, **NON METALLIC**

SIZE 36 - 48

STANDARD EN ISO 20345:2011

UPPER cow suede leather coated, brushed in a thickness of 1,8 - 2,0 mm

LINING laminated breathable fabric **MESH**

INNER INSOLE anatomically shaped from material **EVA** with a high absorbency, antistatic

OUTSOLE **PU/PU** - resistant to fuel oils, antistatic, double density injection, antislip



SPACE comfort



anatomic

DRY SOLE

NON METALLIC

NOTE the upper of the shoe must not come into contact with an aggressive acid or base!



SAFETY SANDAL
FULL GRAIN LEATHER, NON METALLIC



LINCOLN

5115

ORDER NO. 5115-S1P

VERSION S1P SRC - with composite toe cap and kevlar midsole, **NON METALLIC**

SIZE 36 - 48

STANDARD EN ISO 20345:2011

UPPER cowhide leather **NUBUCK** in a thickness of 1,8 - 2,0 mm

LINING laminated breathable fabric **MESH**

INNER INSOLE anatomically shaped from material **EVA** with a high absorbency, antistatic

OUTSOLE **PU/TPU - transparent** - resistant to fuel oils, antistatic, double density injection, antislip



SPACE comfort



anatomic

DRY SOLE

NON METALLIC



SAFETY SHOES - POLYAMIDE FABRIC PUTEK



TAMPERE

5625

ORDER NO.	5625-S3	LINING	laminated breathable fabric MESH
VERSION	S3 SRC - with composite toe cap and kevlar midsole, hydrophobic	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, antislip, antistatic, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	polyamide abrasion resistant fabric PUTEK		



SPACE comfort



anatomic DRY SOLE

PU-TEK



SAFETY SHOES - FULL GRAIN LEATHER



LAUSANNE

5635

ORDER NO.	5635-S1P	LINING	laminated breathable fabric MESH
VERSION	S1P SRC - with composite toe cap and kevlar midsole	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, antislip, antistatic, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm		



SPACE comfort



anatomic DRY SOLE

ANKLE OCCUPATIONAL SHOES
FULL GRAIN LEATHER

SAN MARINO

3170

ORDER NO.	3170-01	LINING	laminated breathable fabric MESH
VERSION	01 FO SRA - without steel toe cap	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, anti-slip, antistatic, double density injection
STANDARD	EN ISO 20347:2012		
UPPER	brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm		



SPACE comfort



anatomic DRY SOLE

LOW CUT OCCUPATIONAL SHOES
FULL GRAIN LEATHER

SOFIE

3175

ORDER NO.	3175-01	LINING	laminated breathable fabric MESH
VERSION	01 FO SRA - without steel toe cap	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, antislip, antistatic, double density injection
STANDARD	EN ISO 20347:2012		
UPPER	brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm		



SPACE comfort



anatomic DRY SOLE

LOW CUT OCCUPATIONAL SHOES - FULL GRAIN LEATHER



SEATTLE

2575

ORDER NO.	2575-01P	LINING	laminated breathable fabric MESH
VERSION	01P FO SRA - without steel toe cap, anti puncture kevlar insole	INNER INSOLE	HI-POLY - padded, anatomically shaped, made of porous polyurethane foam, coated with fabric MESH, antistatic
SIZE	39 - 47	OUTSOLE	PU/PU - resistant to fuel oils, antislip, antistatic, double density injection
STANDARD	EN ISO 20347:2012		
UPPER	brushed cow suede leather VELOUR in a thickness of 1,7 - 1,9 mm		



MIDDLE ANKLE OCCUPATIONAL SHOES - FULL GRAIN LEATHER



RICHMOND

2585

ORDER NO.	2585-01	LINING	laminated breathable fabric MESH
VERSION	01 FO SRA - without steel toe cap	INNER INSOLE	HI-POLY - padded, anatomically shaped, made of porous polyurethane foam, coated with fabric MESH, antistatic
SIZE	36 - 47	OUTSOLE	PU/PU - resistant to fuel oils, antislip, antistatic, double density injection
STANDARD	EN ISO 20347:2012		
UPPER	brushed cow suede leather VELOUR in a thickness of 1,7 - 1,9 mm		



MIDDLE ANKLE OCCUPATIONAL AND SAFETY SHOES
FULL GRAIN LEATHER

MADISON

2595

ORDER NO. 2595-01 | 2595-S1

VERSION 01 01 FO SRA - without steel toe cap

VERSION S1 S1 SRA - with steel toe cap

SIZE 01: 36 - 47 | S1: 39 - 47

STANDARD 01: EN ISO 20347:2012
S1: EN ISO 20345:2011UPPER dry mild cowhide leather **NUBUCK**
in a thickness of 1,8 - 2,0 mmLINING laminated breathable fabric **MESH**INNER **HI-POLY** - padded, anatomically
INSOLE shaped, made of porous polyurethane
foam, coated with fabric **MESH**,
antistaticOUTSOLE **PU/PU** - resistant to fuel oils, antislip,
antistatic, double density injectionLOW CUT OCCUPATIONAL SHOES
LEATHER COMBINED WITH TEXTILE

TIRANA

3195

ORDER NO. 3195-01

VERSIO 01 FO SRA - without steel
toe cap

SIZE 36 - 48

STANDARD EN ISO 20347:2012

UPPER brushed cowhide leather
VELOUR in a thickness
of 1,7 - 1,9 mmLINING laminated breathable fabric **MESH**INNER **HI-POLY** - anatomically shaped,
INSOLE lightweight polyurethane foam coated
with fabric **MESH**, antistaticOUTSOLE **PU/PU - transparent** - resistant
to fuel oils, antislip, antistatic, double
density injection

LOW CUT SAFETY SHOES
LEATHER COMBINED WITH TEXTILE



ROMA

2665

ORDER NO. 2665-S1

VERSION S1 SRC - with steel toe cap

SIZE 36 - 48

STANDARD EN ISO 20345:2011

UPPER brushed cow suede leather
VELOUR in a thickness
of 1,7 - 1,9 mm

LINING laminated breathable fabric MESH

INNER INSOLE anatomically shaped from material
EVA with a high absorbency,
antistatic

OUTSOLE PU/PU - transparent - resistant
to fuel oils, antistatic, double
density injection, antislip



ANKLE SAFETY SHOES
LEATHER COMBINED WITH TEXTILE



LISABON

2660

ORDER NO. 2660-S1

VERSION S1 SRC - with steel toe cap

SIZE 36 - 48

STANDARD EN ISO 20345:2011

UPPER brushed cow suede leather
VELOUR in a thickness
of 1,7 - 1,9 mm

LINING laminated breathable fabric MESH

INNER INSOLE anatomically shaped from material
EVA with a high absorbency,
antistatic

OUTSOLE PU/PU - transparent - resistant
to fuel oils, antistatic, double
density injection, antislip



LOW CUT OCCUPATIONAL SHOES
FULL GRAIN LEATHER



VALENCIA

2995

ORDER NO.	2995-01	LINING	laminated breathable fabric MESH
VERSION	01 FO SRC - without steel toe cap	INNER INSOLE	anatomically shaped from material EVA with a high absorbency, antistatic
SIZE	36 - 48		
STANDARD	EN ISO 20347:2012	OUTSOLE	PU/PU - transparent - resistant to fuel oils, antistatic, double density injection, antislip
UPPER	brushed cow suede leather VELOUR in a thickness of 1,7 - 1,9 mm		



SPACE comfort



anatomic DRY SOLE



ANKLE OCCUPATIONAL SHOES
FULL GRAIN LEATHER



MADRID

2990

ORDER NO.	2990-01	LINING	laminated breathable fabric MESH
VERSION	01 FO SRC - without steel toe cap	INNER INSOLE	anatomically shaped from material EVA with a high absorbency, antistatic
SIZE	36 - 48		
STANDARD	EN ISO 20347:2012	OUTSOLE	PU/PU - transparent - resistant to fuel oils, antistatic, double density injection, antislip
UPPER	brushed cow suede leather VELOUR in a thickness of 1,7 - 1,9 mm		



SPACE comfort



anatomic DRY SOLE

LOW CUT OCCUPATIONAL SHOES
FARMER - FULL GRAIN LEATHER



VALLETTA

2775

ORDER NO.	2775-01	LINING	CAMBRELLA fabric with absorbency
VERSION	01 FO SRC - without steel toe cap	INNER INSOLE	anatomically shaped with latex heel pad, coated with CAMBRELLA, antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, antislip, antistatic, double density injection
STANDARD	EN ISO 20347:2012		
UPPER	cowhide leather NUBUCK in a thickness of 1,8 - 2,0 mm		



SPACE comfort

FORCED CIRCULATION

anatomic DRY SOLE

NOTE color divergence of the material is not a fault



ANKLE OCCUPATIONAL SHOES
FARMER - FULL GRAIN LEATHER | WINTER DESIGN



VADUZ

2770

ORDER NO.	2770-01 2770-02W	LINING 01	CAMBRELLA fabric with absorbency
VERSION 01	01 FO SRC - without steel toe cap	LINING 02W	hair plush DELTA
VERSION 02W	02W FO SRC - without steel toe cap, hydrophobic, winter design	INNER INSOLE	anatomically shaped with latex heel pad, coated with CAMBRELLA, antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, antislip, antistatic, double density injection
STANDARD	EN ISO 20347:2012		
UPPER	cowhide leather NUBUCK in a thickness of 1,8 - 2,0 mm		

NOTE color divergence of the material is not a fault



SPACE comfort

FORCED CIRCULATION

anatomic DRY SOLE

ANKLE OUTDOOR SHOES - FULL GRAIN LEATHER



WINNIPEG

4900

ORDER NO.	4900-40	LINING	breathable thermo-insulation MEMBRANE FREE-TEX®
VERSION	brown colour, FREE-TEX®	INNER INSOLE	expanded polyurethane of high absorbency, antistatic
SIZE	40 - 47	OUTSOLE	EVA/RUBBER - glued construction
USABILITY	shoes suitable for daily wear and outdoor activities		
UPPER	cowhide leather PULL-UP in a thickness of 1,7 - 1,9 mm		



NOTE color divergence of the material is not a fault

ANKLE OCCUPATIONAL SHOES
FULL GRAIN LEATHER - WINTER DESIGN

SAN MARINO

3170

ORDER NO.	3170-01W	LINING	hair plush DELTA
VERSION	01W FO SRC - without steel toe cap, winter design	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, anti-slip, antistatic, double density injection
STANDARD	EN ISO 20347:2012		
UPPER	brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm		



SAFETY SANDAL - FULL GRAIN LEATHER



HAAG

5335


ORDER NO.	5335-S1P	LINING	laminated breathable fabric MESH
VERSION	S1P SRA - with composite toe cap and kevlar midsole	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	PU/TPU - transparent - resistant to fuel oils, antislip, antistatic, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	cowhide leather CRAZY HORSE in a thickness of 2,0 - 2,2 mm		



SPACE comfort



anatomic DRY SOLE



SAFETY SANDAL ESD - FULL GRAIN LEATHER



LYON

2225

ORDER NO.	2225-S1ESD	LINING	laminated breathable fabric MESH
VERSION	S1 ESD SRC - with aluminium toe cap - antistatic properties ESD	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, antislip, antistatic, double density injection
STANDARD	EN ISO 20345:2011 EN ISO 61340-5-1:2016		
UPPER	cow suede leather, coated, brushed in a thickness of 1,8 - 2,0 mm		



SPACE comfort



anatomic DRY SOLE

ANKLE SAFETY SHOES
FULL GRAIN LEATHER IN A COMBINATION WITH RUBBER



BALTIMORE

4980

ORDER NO.	4980-S3	LINING	laminated breathable fabric MESH
VERSION	S3 SRC - with composite toe cap and kevlar midsole, hydrophobic	INNER INSOLE	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	40 - 47	OUTSOLE	EVA/RUBBER - resistant to fuel oils, antistatic, antislip, glued construction, with high rubber occupancy
STANDARD	EN ISO 20345:2012		
UPPER	cowhide leather CRAZY HORSE in a thickness of 1,7 - 1,9 mm		



OCCUPATIONAL BOOTS
FULL GRAIN LEATHER IN A COMBINATION WITH RUBBER



WELLINGTON

4390

ORDER NO.	4390-08	LINING	textile, thermo-insulation FLEECE
VERSION	OB E SRA - without steel toe cap	INNER INSOLE	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	38 - 48	OUTSOLE	EVA/RUBBER - antistatic, antislip, glued construction, with high rubber occupancy
STANDARD	EN ISO 20347:2012		
UPPER	brushed cowhide suede leather VELOUR in a thickness of 1,7 - 1,9 mm		



