

Hard & Heavy



3 X
ABOVE THE
STANDARD

INNER INSOLE
WATER
ABSORPTION

3 X
ABOVE THE
STANDARD

FREE-TEX® LINING
WATER PERMEABILITY
COEFFICIENT

2 X
ABOVE THE
STANDARD

FREE-TEX® LINING
WATER VAPOR
PERMEABILITY

2 X
ABOVE THE
STANDARD

**UPPER FULLGRAIN
COW LEATHER**
STRENGTH IN TEAR OF CHINK

In the **Hard & Heavy** category, we offer footwear suitable for heavy industry, steel production and processing, engineering operations, smelters, foundries, freezers, construction, demanding outdoor environments with fuels and oils, highly polluted environments. The full functionality of

the footwear is ensured by the used natural upper materials. We bring part of the collection in this category with unique **MICHELIN® Technical Soles**, **FREE-TEX® lining**, membrane **GORE-TEX®** and also with the unique patented **BOA® Fit System**.

SOLES
BY



MICHELIN® TECHNICAL SOLES

The outsoles are equipped with a combination of specially designed rubber compounds and are inspired by unique technical design of world famous brands Michelin® tires



powered by BOA FIT® SYSTEM

Unique system of closing footwear



FREE-TEX® LINING

Vapor-permeable, water-resistant membrane



HARD HEEL STRUCTURED

Modern solutions of the heel shoe part, which ensures maximal stabilization of the foot while walking and standing



HRO

The outsoles resistant to fuel oils and contact heat HRO up to 300 °C



MEMBRANE GORE-TEX®

Vapor-permeable, waterproof GORE-TEX® membrane



ANATOMIC DRY SOLE

Anatomically shaped insole with excellent absorbency and dryness



NON METALIC

Shoes without any metal components suitable for area that require it



SPACE COMFORT

Optimized ergonomics and shoe width



METATARSAL

Special protection system of the vamp, designated for the area of smelters, foundries, etc.



FORCED CIRCULATION

Exhaust ventilation system combined with lining with absorbent capability.

These shoes are "breathing" and provide maximum comfort



ALWAYS A STEP AHEAD

HARD & HEAVY



SAFETY ANKLE SHOES - FULL GRAIN LEATHER
 WITH ANKLE PROTECTION, GORE-TEX® MEMBRANE,
 POWERED BY BOA® FIT SYSTEM, MICHELIN® TECHNICAL SOLES



VERMONT

7780



ORDER NO. 7780-S7L

VERSION S7L FO HRO AN SR - with composite toe cap and kevlar midsole, hydrophobic, GORE-TEX® membrane, powered by BOA® Fit System, MICHELIN® Technical Soles

SIZE 39 - 48

STANDARD EN ISO 20345:2022

UPPER smooth cowhide leather in a thickness of 2,0 - 2,2 mm

LINNING vapor permeable, waterproof GORE-TEX® membrane

INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic

OUTSOLE MICHELIN®-PU/RUBBER - up to 300°C, HRO, SR, resistant to fuel oils, slip resistant, antistatic



NEW



SAFETY BOOTS - FULL GRAIN LEATHER
WITH ANKLE PROTECTION, GORE-TEX® MEMBRANE,
POWERED BY BOA® FIT SYSTEM, MICHELIN® TECHNICAL SOLES



CONNECTICUT

7790

ORDER NO. 7790-S7L
VERSION S7L FO HRO AN SR - with composite toe cap and kevlar midsole, hydrophobic, GORE-TEX® membrane, powered by BOA® Fit System, MICHELIN® Technical Soles

LINNING vapor permeable, waterproof GORE-TEX® membrane
INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
OUTSOLE MICHELIN®-PU/RUBBER - up to 300°C, HRO, SR, resistant to fuel oils, slip resistant, antistatic

SIZE 39 - 48
STANDARD EN ISO 20345:2022
UPPER smooth cowhide leather in a thickness of 2,0 - 2,2 mm





SAFETY ANKLE SHOES - FULL GRAIN LEATHER
 POWERED BY BOA® FIT SYSTEM, MICHELIN® TECHNICAL SOLES



HARTFORD

6420 /



HARDHEEL
STRUCTURED

SPACE comfort

FORCED CIRCULATION

anatomic DRY SOLE



SOLES BY



ORDER NO. 6420-S3

VERSION **S3 HRO SRC** - with composite toe cap and kevlar midsole, hydrophobic, powered by BOA® Fit System, MICHELIN® Technical Soles

SIZE 39 - 48

STANDARD EN ISO 20345:2011

UPPER smooth cowhide leather in a thickness of 2,0 - 2,2 mm

LINNING laminated breathable fabric **MESH**

INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic

OUTSOLE **MICHELIN®-PU/RUBBER** - up to 300°C, HRO, SRC, resistant to fuel oils, slip resistant, antistatic

SAFETY ANKLE SHOES - FULL GRAIN LEATHER
WATERPROOF FREE-TEX® LINING,
POWERED BY BOA® FIT SYSTEM, MICHELIN® TECHNICAL SOLES



BUFFALO

7130

ORDER NO. 7130-S3

VERSION S3 HRO SRC CI WR - with composite toe cap and kevlar midsole, hydrophobic, waterproof FREE-TEX® lining powered by BOA® Fit System, MICHELIN® Technical Soles

SIZE 39 - 48

STANDARD EN ISO 20345:2011

UPPER cowhide leather CRAZY HORSE in a thickness of 2,0 - 2,2 mm

LINNING thermo-insulating, breathable waterproof FREE-TEX® lining
INNER INSOLE expanded polyurethane of high absorbency, antistatic
OUTSOLE MICHELIN®-PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, slip resistant, antistatic



HARDHEEL STRUCTURED

SPACE COMFORT



anatomic DRY SOLE



SOLES BY



OCCUPATIONAL ANKLE SHOES - FULL GRAIN LEATHER
WATERPROOF FREE-TEX® LINING, POWERED BY BOA® FIT SYSTEM,
MICHELIN® TECHNICAL SOLES, NON METALLIC



BUFFALO

7130

ORDER NO. 7130-02

VERSION O2 FO HRO SRC CI WR - without composite toe cap and kevlar midsole, hydrophobic, waterproof FREE-TEX® lining powered by BOA® Fit System, MICHELIN® Technical Soles, NON METALLIC

SIZE 39 - 48

STANDARD EN ISO 20347:2011

UPPER cowhide leather CRAZY HORSE in a thickness of 2,0 - 2,2 mm

LINNING thermo-insulating, breathable waterproof FREE-TEX® lining
INNER INSOLE expanded polyurethane of high absorbency, antistatic
OUTSOLE MICHELIN®-PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, slip resistant, antistatic



HARDHEEL STRUCTURED

SPACE COMFORT



anatomic DRY SOLE

NON METALLIC



SAFETY ANKLE SHOES - FULL GRAIN LEATHER
 WATERPROOF FREE-TEX® LINING,
 MICHELIN® TECHNICAL SOLES, NON METALLIC



ROCKFORD

7140

ORDER NO. 7140-S3

VERSION S3 S3 HRO SRC CI WR - with composite toe cap and kevlar midsole, hydrophobic, waterproof FREE-TEX® lining, MICHELIN® Technical Soles, NON METALLIC

SIZE 39 - 48

STANDARD EN ISO 20345:2011

UPPER dry mild cow hide leather in a thickness of 2,0 - 2,2 mm

LINING thermo-insulating, breathable waterproof FREE-TEX® lining

INNER INSOLE expanded polyurethane of high absorbency, antistatic

OUTSOLE MICHELIN®-PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, slip resistant, antistatic



HARDHEEL STRUCTURED

SPACE comfort



anatomic DRY SOLE

NON METALLIC



SOLES BY



OCCUPATIONAL AND SAFETY BOOTS - FULL GRAIN LEATHER
 WATERPROOF FREE-TEX® LINING,
 MICHELIN® TECHNICAL SOLES, NON METALLIC



PORTLAND

7190

ORDER NO. 7190-02 | 7190-S3

VERSION 02 02 FO HRO SRC CI WR - without composite toe cap and kevlar midsole, hydrophobic, waterproof FREE-TEX® lining, MICHELIN® Technical Soles, NON METALLIC

VERSION S3 S3 HRO SRC CI WR - with composite toe cap and kevlar midsole, hydrophobic, waterproof FREE-TEX® lining, MICHELIN® Technical Soles, NON METALLIC

SIZE 39 - 48

STANDARD 02: EN ISO 20347:2012 | S3: EN ISO 20345:2011

UPPER cowhide leather CRAZY HORSE in a thickness of 2,0 - 2,2 mm

LINING thermo-insulating, breathable waterproof FREE-TEX® lining

INNER INSOLE expanded polyurethane of high absorbency, antistatic

OUTSOLE MICHELIN®-PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, slip resistant, antistatic



HARDHEEL STRUCTURED

SPACE comfort



anatomic DRY SOLE

NON METALLIC



SOLES BY



OCCUPATIONAL AND SAFETY ANKLE SHOES
 FULL GRAIN LEATHER - WATERPROOF FREE-TEX® LINING



DUBLIN

2440

ORDER NO. 2440-02 | 2440-S3

VERSION 02 **02 FO SRC** - without composite toe cap and kevlar midsole, hydrophobic, waterproof **FREE-TEX®** lining

VERSION S3 **S3 HRO SRC** - with composite toe cap and kevlar midsole, hydrophobic, waterproof **FREE-TEX®** lining, **NON METALLIC**

SIZE 02: 37 - 49 | S3: 39 - 49

STANDARD 02: EN ISO 20347:2012
 S3: EN ISO 20345:2012

UPPER cowhide leather **NUBUCK** in a thickness of 1,9 - 2,1 mm

LINING thermo-insulating, breathable waterproof **FREE-TEX®** lining

INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic

OUTSOLE 02 **PU/TPU** - resistant to fuel oils, antistatic, antislip, double density injection

OUTSOLE S3 **PU/RUBBER** - up to 300°C, resistant to fuel oils, antistatic, slip resistant, double density injection



NON METALLIC



OCCUPATIONAL BOOTS
 FULL GRAIN LEATHER - WATERPROOF FREE-TEX® LINING



BOGOTA

2470

ORDER NO. 2470-02

VERSION 02 **FO SRC** - without steel toe cap, hydrophobic, waterproof **FREE-TEX®** lining

SIZE 37 - 48

STANDARD EN ISO 20347:2011

UPPER cowhide leather **NUBUCK** in a thickness of 1,9 - 2,1 mm

NOTE divergence of the material color shades is not a fault

LINING thermo-insulating, breathable waterproof **FREE-TEX®** lining

INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic

OUTSOLE **PU/TPU** - resistant to fuel oils, antistatic, slip resistant, double density injection



SAFETY SANDALS - FULL GRAIN LEATHER



OREGON

2705

ORDER NO.	2705-S1P	LINING	laminated breathable fabric MESH
VERSION	S1 P HRO SRC - with composite toe cap and kevlar midsole	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, slip resistant, antistatic, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	cowhide leather in a thickness of 2,0 - 2,2 mm		



SAFETY LOW SHOES - FULL GRAIN LEATHER



MISSOURI

2715

ORDER NO.	2715-S3	LINING	laminated breathable fabric MESH
VERSION	S3 HRO SRC - with composite toe cap and kevlar midsole, hydrophobic	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, slip resistant, antistatic, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	cowhide leather in a thickness of 2,0 - 2,2 mm		





SAFETY ANKLE SHOES
FULL GRAIN LEATHER

HALIFAX

2710

ORDER NO.	2710-S3	LINING	laminated breathable fabric MESH
VERSION	S3 HRO SRC - with composite toe cap and kevlar midsole, hydrophobic	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	36 - 48	OUTSOLE	PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, slip resistant, antistatic, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	cowhide leather in a thickness of 2,0 - 2,2 mm		



HARD & HEAVY



OCCUPATIONAL AND SAFETY ANKLE SHOES
FULL GRAIN LEATHER



HANNOVER

2720

ORDER NO.	2720-02 2720-S3	UPPER	cowhide leather CRAZY HORSE in a thickness of 1,9 - 2,1 mm
VERSION 02	02 FO SRC - without composite toe cap and kevlar midsole, hydrophobic	LINING	laminated breathable fabric MESH
VERSION S3	S3 SRC - with composite toe cap and kevlar midsole, hydrophobic	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection
STANDARD	02: EN ISO 20347:2012 S3: EN ISO 20345:2011		



OCCUPATIONAL AND SAFETY LOW SHOES
FULL GRAIN LEATHER



COVENTRY

5065

ORDER NO. 5065-01 | 5065-S1
VERSION 01 01 FO HRO SR - without steel toe cap
VERSION S1 S1 HRO SRC - with steel toe cap
SIZE 36 - 48
STANDARD 01: EN ISO 20347:2022
 S1: EN ISO 20345:2011
UPPER cowhide leather with a pattern in a thickness of 1,8 - 2,0 mm

LINING laminated breathable fabric MESH
INNER INSOLE anatomically shaped from material EVA with a high absorbency, antistatic
OUTSOLE PU/RUBBER - up to 300°C, HRO, resistant to fuel oils, antistatic, slip resistant, double density injection



OCCUPATIONAL AND SAFETY ANKLE SHOES
FULL GRAIN LEATHER



NORWICH

5070

ORDER NO. 5070-02 | 5070-S3
VERSION 02 02 FO HRO SR - without composite toe cap and midsole, hydrophobic
VERSION S3 S3 HRO WR SRC - with composite toe cap and kevlar midsole, hydrophobic
SIZE 36 - 48
STANDARD 02: EN ISO 20347:2022
 S3: EN ISO 20345:2011
UPPER cowhide leather with a pattern in a thickness of 1,8 - 2,0 mm

LINING laminated breathable fabric MESH
INNER INSOLE anatomically shaped from material EVA with a high absorbency, antistatic
OUTSOLE PU/RUBBER - up to 300°C, HRO, resistant to fuel oils, antistatic, slip resistant, double density injection



SAFETY ANKLE SHOES - FULL GRAIN LEATHER
WATERPROOF FREE-TEX® LINING, NON METALLIC



DALLAS

5430

ORDER NO.	5430-S3	LINING	thermo-insulating, breathable waterproof FREE-TEX® lining
VERSION	S3 HRO WR CI SRC - with composite toe cap and kevlar midsole, hydrophobic, waterproof FREE-TEX® lining, NON METALLIC	INNER INSOLE	anatomically shaped from material EVA with a high absorbency, antistatic
SIZE	36 - 48	OUTSOLE	PU/RUBBER - up to 300°C, HRO, SRC resistant to fuel oils, antistatic, slip resistant, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	smooth cowhide leather in a thickness of 2,0 - 2,2 mm		



HARD & HEAVY

SAFETY BOOTS - FULL GRAIN LEATHER
WATERPROOF FREE-TEX® LINING, NON METALLIC



HOUSTON

5490

ORDER NO.	5490-S3	LINING	thermo-insulating, breathable waterproof FREE-TEX® lining
VERSION	S3 HRO WR CI SRC - with composite toe cap and kevlar midsole, hydrophobic, waterproof FREE-TEX® lining, NON METALLIC	INNER INSOLE	anatomically shaped from material EVA with a high absorbency, antistatic
SIZE	36 - 48	OUTSOLE	PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, slip resistant, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	smooth cowhide leather in a thickness of 2,0 - 2,2 mm		



SAFETY ANKLE SHOES
FULL GRAIN LEATHER - DIELECTRIC



WASHINGTON

6400

ORDER NO. 6400-SBP

VERSION SB P HRO SRC - with composite toe cap and kevlar midsole - the lower part of the footwear is resistant to electric shock at a voltage up to **10 kV** according to **EN 50321**

SIZE 40 - 47

STANDARD EN ISO 20345:2011 | EN 50321

UPPER cowhide leather coated, brushed in a thickness of 1,8 - 2,0 mm

LINING laminated breathable fabric **MESH**

INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**

OUTSOLE **PU/RUBBER** - up to 300°C, HRO, SRC, resistant to fuel oils, slip resistant

NOTE the upper of the shoe must not come into contact with an aggressive acid or base!



SAFETY LOW SHOES
FULL GRAIN LEATHER - DIELECTRIC



PENNSYLVANIA

6405

ORDER NO. 6405-SBP

VERSION SB P HRO SRC - with composite toe cap and kevlar midsole - the lower part of the footwear is resistant to electric shock at a voltage up to **10 kV** according to **EN 50321**

SIZE 40 - 47

STANDARD EN ISO 20345:2011 | EN 50321

UPPER cowhide leather coated, brushed in a thickness of 1,8 - 2,0 mm

LINING laminated breathable fabric **MESH**

INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**

OUTSOLE **PU/RUBBER** - up to 300°C, HRO, SRC, resistant to fuel oils, slip resistant

NOTE the upper of the shoe must not come into contact with an aggressive acid or base!



SAFETY ANKLE SHOES - FULL GRAIN LEATHER
WITH INSTEP PROTECTION



BOLTON

5080

ORDER NO.	5080M-S3	LINING	laminated breathable fabric MESH
VERSION	S3L FO HRO SR - with composite toe cap and kevlar midsole, hydrophobic	INNER INSOLE	anatomically shaped from material EVA with a high absorbency, antistatic
SIZE	38 - 48	OUTSOLE	PU/RUBBER - up to 300°C, HRO, SR, resistant to fuel oils, antistatic, slip resistant, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	cowhide leather with a pattern in a thickness of 1,8 - 2,0 mm		



HARD & HEAVY



SAFETY ANKLE SHOES - FULL GRAIN LEATHER
WITH INSTEP PROTECTION, NON METALLIC



REYKJAVIK

2480

ORDER NO.	2480-S3M	LINING	laminated breathable fabric MESH
VERSION	S3 M HRO SRC - with composite toe cap and kevlar midsole, hydrophobic, METATARSAL , NON METALLIC	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	38 - 48	OUTSOLE	PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, antistatic, slip resistant, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	cowhide leather with a pattern in a thickness of 2,0 - 2,2 mm		



SAFETY LOW SHOES - FULL GRAIN LEATHER



ANDORRA

2315

ORDER NO.	2315-S3	LINING	laminated breathable fabric MESH
VERSION	S3 HRO SRC - with steel toe cap and midsole, hydrophobic	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	37 - 48	OUTSOLE	PU/RUBBER - up to 300°C, HRO, SRC resistant to fuel oils, antistatic, slip resistant, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	cowhide leather in a thickness of 2,0 - 2,2 mm		



SAFETY ANKLE SHOES - FULL GRAIN LEATHER



LUXEMBURG

2310

ORDER NO.	2310-S3	LINING	laminated breathable fabric MESH
VERSION	S3 HRO SRC - with steel toe cap and midsole, hydrophobic	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	37 - 49	OUTSOLE	PU/RUBBER - up to 300°C, HRO, SRC resistant to fuel oils, antistatic, slip resistant, double density injection
STANDARD	EN ISO 20345:2011		
UPPER	cowhide leather in a thickness of 2,0 - 2,2 mm		



SAFETY ANTICUT BOOTS
CHAIN SAW RESISTANT - FULL GRAIN LEATHER



BELFAST

2350

ORDER NO. 2350-S3

VERSION S3 WR HRO SRC CI ANTICUT LEVEL 1 - with steel toe cap and midsole, hydrophobic, anticut kevlar lining, kevlar sewing

SIZE 39 - 47

STANDARD EN ISO 20345:2011 | EN ISO 17249

UPPER cowhide leather with pattern in a thickness of 2,0 - 2,2 mm

LINING laminated fabric **CAMBRELLA**

INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic

OUTSOLE **PU/RUBBER** - up to 300°C, HRO, SRC, resistant to fuel oils, antistatic, slip resistant, double density injection



SAFETY BOOTS
FULL GRAIN LEATHER



LONDON

2330

ORDER NO. 2330-S3

VERSION S3 CI SRC - with steel toe cap and midsole, hydrophobic

SIZE 37 - 49

STANDARD EN ISO 20345:2011

UPPER cowhide leather with a pattern in a thickness of 2,0 - 2,2 mm

LINING thermo-insulation fabric **3M THINSULATE**

INNER INSOLE **HI-POLY** - anatomically formed, coated with **CAMBRELLA**, antistatic

OUTSOLE **PU/TPU** - resistant to fuel oils, antistatic, slip resistant





GLASGOW

2390

ORDER NO. 2390-02 | 2390-S3
VERSION O2 O2 FO HRO SRC - without toe cap and midsole, hydrophobic
VERSION S3 S3 HRO SRC - with steel toe cap and midsole, hydrophobic
SIZE 37 - 48
STANDARD O2: EN ISO 20347:2012
 S3: EN ISO 20345:2011
UPPER cowhide leather in a thickness of 2,0 - 2,2 mm

LINING laminated fabric FLESH
INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
OUTSOLE PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, antistatic, slip resistant, double density injection



SAFETY BOOTS - FULL GRAIN LEATHER



MARYLAND

2790

ORDER NO. 2790-S3
VERSION S3 HRO SRC - with composite toe cap and kevlar midsole, hydrophobic
SIZE 36 - 48
STANDARD EN ISO 20345:2011
UPPER cowhide leather in a thickness of 2,0 - 2,2 mm

LINING laminated breathable fabric MESH
INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
OUTSOLE PU/RUBBER - up to 300°C, HRO, SRC resistant to fuel oils, slip resistant, antistatic, double density injection



ANKLE OCCUPATIONAL AND SAFETY SHOES
FULL GRAIN LEATHER



QUITO

2490

ORDER NO. 2490-01 | 2490-S1
VERSION 01 01 FO HRO SR - without toe cap
VERSION S1 S1 HRO SRC - with steel toe cap
SIZE 01: 40 - 48 | S1: 39 - 48
STANDARD 01: EN ISO 20347:2022
 S1: EN ISO 20345:2011
UPPER cowhide leather with a pattern
 in a thickness of 2,0 - 2,2 mm

LINING laminated breathable
fabric MESH
**INNER
INSOLE** HI-POLY - anatomically shaped,
lightweight polyurethane foam
coated with fabric MESH,
antistatic
OUTSOLE PU/RUBBER - up to 300°C, HRO,
resistant to fuel oils, antistatic,
slip resistant, double density
injection



HARD & HEAVY



SAFETY RUBBER BOOTS
WITH INSTEP PROTECTION



SAN DIEGO

1010

ORDER NO. 1010-S5
VERSION S5 SRA - with toe cap
and steel midsole
SIZE 40 - 47
STANDARD EN ISO 20345:2011
UPPER PVC/NITRIL

**INNER
INSOLE** HI-POLY - anatomically shaped,
lightweight polyurethane foam
coated with fabric MESH, antistatic
OUTSOLE PVC/NITRIL

