

Work & Tight



3X
ABOVE THE
STANDARD

INNER INSOLE
WATER
ABSORPTION

13X
ABOVE THE
STANDARD

UPPER VELOUR
WATER VAPOR
PERMEABILITY

7X
ABOVE THE
STANDARD

UPPER VELOUR
WATER PERMEABILITY
COEFFICIENT

2X
ABOVE THE
STANDARD

UPPER VELOUR
STRENGTH IN THE
FURTHER TEARING

19X
ABOVE THE
STANDARD

UPPER MICROFIBER
WATER VAPOR
PERMEABILITY

8X
ABOVE THE
STANDARD

UPPER MICROFIBER
WATER PERMEABILITY
COEFFICIENT

In the **Work & Tight** category, we offer footwear with an ultralight construction (**ULTRALIGHT**), which is suitable for light environments, predominantly dry, indoor areas, clean operations, **ESD** environments, assembly halls, technical professions.

We bring part of the collection in this category with the unique **MICHELIN® Technical Soles** and also with the unique, patented **BOA® Fit System**.



MEMBRANE GORE-TEX®
Vapor-permeable,
waterproof GORE-TEX®
membrane



**POWERED BY
BOA FIT® SYSTEM**
Unique system
of closing shoes



FORCED CIRCULATION
Exhaust ventilation system
combined with lining with
absorbent capability. These
shoes are "breathing" and
provide maximum comfort

SOLES
BY



MICHELIN® Technical Soles
The outsoles are equipped with
a combination
of specially designed rubber
compounds and are inspired
by unique technical design
of world famous brands
Michelin® tires

NON METALLIC

NON METALLIC
Shoes without any metal
components suitable for area
that require it



MICROFIBER
Upper HIGH-TECH material
composed of microfibers,
reaching the appearance,
breathability, water resistance
and parameters of the natural
leather

**anatomic
DRY SOLE**

ANATOMIC DRY SOLE
Anatomically shaped insole
with excellent absorbency
and dryness



SPACE COMFORT
Optimized ergonomics
and shoe width



ESD
Antistatic
ESD properties



WORK & TIGHT



SAFETY ANKLE SHOES - MICROFIBER
GORE-TEX® MEMBRANE, POWERED BY BOA® FIT SYSTEM

LIVERPOOL

8010

ORDER NO. 8010-S7L

VERSION S7L FO SR - with composite toe cap and kevlar midsole, hydrophobic, GORE-TEX® membrane, powered by BOA® Fit System

SIZE 37 - 48

STANDARD EN ISO 20345:2022

UPPER breathable poromeric **microfiber** material

LINNING vapor permeable, waterproof GORE-TEX® membrane

INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic

OUTSOLE PU/TPU - SR, resistant to fuel oils, slip resistant, antistatic



NEW



SAFETY ANKLE SHOES - MICROFIBER
GORE-TEX® MEMBRANE



BIRMINGHAM

8020

ORDER NO. 8020-S7L

VERSION S7L FO SR - with composite toe cap and kevlar midsole, hydrophobic, GORE-TEX® membrane

SIZE 37 - 48

STANDARD EN ISO 20345:2022

UPPER breathable poromeric **microfiber** material

LINNING vapor permeable, waterproof GORE-TEX® membrane

INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic

OUTSOLE PU/TPU - SR, resistant to fuel oils, slip resistant, antistatic



NEW



SAFETY LOW SHOES ESD - MICROFIBER
POWERED BY BOA® FIT SYSTEM, ULTRALIGHT



CALIFORNIA

2295

ORDER NO. 2295-S3BOA
VERSION S3 ESD SRC - with composite toe cap and kevlar midsole, hydrophobic - Tantistatic properties ESD, powered by BOA® Fit System
SIZE 36 - 49
STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016
UPPER brushed, breathable pomeric microfiber material

LINING laminated breathable fabric MESH
INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
OUTSOLE PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection



ULTRALIGHT



WORK & TIGHT

SAFETY ANKLE SHOES ESD - MICROFIBER
POWERED BY BOA® FIT SYSTEM, ULTRALIGHT



WISCONSIN

2290

ORDER NO. 2290-S3BOA
VERSION S3 ESD SRC - with composite toe cap and kevlar midsole, hydrophobic - antistatic properties ESD, NON METALLIC, powered by BOA® Fit System
SIZE 36 - 49
STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016
UPPER brushed, breathable pomeric microfiber material

LINING laminated breathable fabric MESH
INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
OUTSOLE PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection



ULTRALIGHT

SAFETY SANDALS ESD
MICROFIBER, NON METALLIC, ULTRALIGHT



EDMONTON

2275

ORDER NO. 2275-S1PESD
VERSION S1 P ESD SRC - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC
SIZE 36 - 49
STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016
UPPER brushed, breathable poromeric microfiber material

LINING laminated breathable fabric MESH
INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
OUTSOLE PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection



ULTRALIGHT



OCCUPATIONAL AND SAFETY LOW SHOES ESD
MICROFIBER, NON METALLIC, ULTRALIGHT



CHICAGO

2285

ORDER NO. 2285-01ESD | 2285-S1PESD
VERSION 01: 01 FO ESD SRC - without composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC
VERSION S1P: S1 P ESD SRC - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC
SIZE 36 - 49
STANDARD 01: EN ISO 20347:2012
S1P: EN ISO 20345:2011
ESD: EN ISO 61340-5-1:2016
UPPER brushed, breathable poromeric microfiber material

LINING laminated breathable fabric MESH
INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
OUTSOLE PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection



ULTRALIGHT

SAFETY LOW SHOES ESD - MICROFIBER
NON METALLIC, ULTRALIGHT



CALIFORNIA

2295

ORDER NO. 2295-S3ESD
VERSION S3 ESD SRC - with composite toe cap and kevlar midsole, hydrophobic - antistatic properties **ESD, NON METALLIC**
SIZE 36 - 49
STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016
UPPER brushed, breathable poromeric **microfiber** material

LINING laminated breathable fabric **MESH**
INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic
OUTSOLE **PU/PU** - resistant to fuel oils, slip resistant, antistatic, double density injection



ULTRALIGHT



WORK & TIGHT

SAFETY ANKLE SHOES ESD - MICROFIBER
NON METALLIC, ULTRALIGHT



WISCONSIN

2290

ORDER NO. 2290-S3ESD
VERSION S3 ESD SRC - with composite toe cap and kevlar midsole, hydrophobic - antistatic properties **ESD, NON METALLIC**
SIZE 36 - 49
STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016
UPPER brushed, breathable poromeric **microfiber** material

LINING laminated breathable fabric **MESH**
INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic
OUTSOLE **PU/PU** - resistant to fuel oils, slip resistant, antistatic, double density injection



ULTRALIGHT

SAFETY LOW SHOES ESD
 POLYAMIDE FABRIC PUTEK,
 MICHELIN® TECHNICAL SOLES, NON METALLIC



MILWAUKEE

8185

ORDER NO. 8185-S3ESD

VERSION S3 ESD SRC - with composite toe cap and kevlar midsole - antistatic properties **ESD, NON METALLIC** MICHELIN® Technical Soles

SIZE 36 - 47

STANDARD EN ISO 20345:2011 | EN ISO 61340-5-1:2016

UPPER polyamide abrasion resistant fabric **PUTEK**

LINNING laminated breathable fabric **MESH**

INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic

OUTSOLE **MICHELIN® PU/RUBBER** - resistant to fuel oils, slip resistant, antistatic



DRY SOLE NON METALLIC

SOLES BY



PUTEK



SAFETY ANKLE SHOES ESD
 POLYAMIDE FABRIC PUTEK,
 MICHELIN® TECHNICAL SOLES, NON METALLIC



SACRAMENTO

8180

ORDER NO. 8180-S3ESD

VERSION S3 ESD SRC - with composite toe cap and kevlar midsole - antistatic properties **ESD, NON METALLIC** MICHELIN® Technical Soles

SIZE 36 - 47

STANDARD EN ISO 20345:2011 | EN ISO 61340-5-1:2016

UPPER polyamide abrasion resistant fabric **PUTEK**

LINNING laminated breathable fabric **MESH**

INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic

OUTSOLE **MICHELIN® PU/RUBBER** - resistant to fuel oils, slip resistant, antistatic



DRY SOLE NON METALLIC

SOLES BY



PUTEK

SAFETY LOW SHOES ESD - FULL GRAIN LEATHER
MICHELIN® TECHNICAL SOLES, NON METALLIC



INDIANA

8125

ORDER NO.	8125-S1PLESD	LINNING	SOFT-LINNER - stretch, breathable with absorbency
VERSION	S1 PL ESD FO SR - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC, MICHELIN® Technical Soles	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	36 - 47	OUTSOLE	MICHELIN® PU/RUBBER - resistant to fuel oils, slip resistant, antistatic
STANDARD	EN ISO 20345:2022 EN ISO 61340-5-1:2016		
UPPER	brushed cow suede leather VELOUR in a thickness of 1,7 - 1,9 mm		



HARDHEEL STRUCTURED

SPACE COMFORT

FORCED CIRCULATION

anatomic

DRY SOLE NON METALLIC

SOLES BY



WORK & TIGHT



SAFETY LOW SHOES - FULL GRAIN LEATHER
MICHELIN® TECHNICAL SOLES, NON METALLIC



DAKOTA

8135

ORDER NO.	8135-S1	LINNING	laminated breathable fabric MESH
VERSION	S1 FO SR - with composite toe cap, NON METALLIC, MICHELIN® Technical Soles	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	36 - 47	OUTSOLE	MICHELIN® PU/RUBBER - resistant to fuel oils, slip resistant, antistatic
STANDARD	EN ISO 20345:2022		
UPPER	cowhide leather CRAZY HORSE i n a thickness of 1,8 - 2,0 mm		



SPACE COMFORT

FORCED CIRCULATION

anatomic

DRY SOLE NON METALLIC

SOLES BY



SAFETY LOW SHOES ESD - TEXTILE
WITH CPU PRINT, MICHELIN® TECHNICAL SOLES



KENTUCKY

8145

ORDER NO. 8145-S1PLESD

VERSION S1 PL ESD FO SR - with composite toe cap and kevlar midsole - antistatic properties ESD MICHELIN® Technical Soles

SIZE 36 - 47

STANDARD EN ISO 20345:2022 | EN ISO 61340-5-1:2016

UPPER abrasion resistant, breathable textile with CPU print

LINNING laminated breathable fabric MESH

INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic

OUTSOLE MICHELIN® PU/RUBBER - resistant to fuel oils, slip resistant, antistatic



SAFETY SANDALS ESD - FULL GRAIN LEATHER
NON METALLIC, MICHELIN® TECHNICAL SOLES



VANCOUVER

8115

ORDER NO. 8115-S1PLESD

VERSION S1 PL ESD FO SR - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC, MICHELIN® Technical Soles

SIZE 36 - 47

STANDARD EN ISO 20345:2022 | EN ISO 61340-5-1:2016

UPPER cow leather, coated, brushed in a thickness of 1,8 - 2,0 mm

LINNING laminated breathable fabric MESH

INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic

OUTSOLE MICHELIN® PU/RUBBER - resistant to fuel oils, slip resistant, antistatic

NOTE the upper of the shoe must not come into contact with an aggressive acid or base!



SAFETE ANKLE SHOES ESD
MICROFIBER, NON METALLIC, ULTRALIGHT



QUEBEC

2230

ORDER NO. 2230-S1PESD
VERSION S1 P ESD SRC - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC
SIZE 36 - 49
STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016
UPPER brushed, breathable poromeric microfiber material

LINING laminated breathable fabric MESH
INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
OUTSOLE PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection



SPACE comfort

FORCED CIRCULATION

anatomic DRY SOLE

NON METALLIC



ULTRALIGHT



WORK & TIGHT

OCCUPATIONAL ANKLE SHOES - FULL GRAIN LEATHER
MICHELIN® TECHNICAL SOLES



BONN

8190

ORDER NO. 8190-01PL
VERSION 01 PL FO SR - without composite toe cap, anti puncture kevlar midsole MICHELIN® Technical Soles
SIZE 39 - 47
STANDARD EN ISO 20347:2022
UPPER brushed cow suede leather VELOUR in a thickness of 1,8 - 2,0 mm

LINING laminated breathable fabric MESH
INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
OUTSOLE MICHELIN®-PU/RUBBER - SR, resistant to fuel oils, slip resistant, antistatic



SPACE comfort

FORCED CIRCULATION

anatomic DRY SOLE

SOLES BY MICHELIN

SAFETY SANDALS ESD
FULL GRAIN LEATHER, NON METALLIC



LIVORNO

2025

ORDER NO.	2025-S1PLESD	LINING	laminated breathable fabric MESH
VERSION	S1 PL ESD SR - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	36 - 49	OUTSOLE	PU/PU - slip resistant, antistatic, double density injection
STANDARD	EN ISO 20345:2022 EN ISO 61340-5-1:2016		
UPPER	brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm		



SAFETY SANDALS ESD
FULL GRAIN LEATHER, NON METALLIC



BOLOGNA

2035

ORDER NO.	2035-S1PLESD	LINING	laminated breathable fabric MESH
VERSION	S1 PL ESD SR - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	36 - 49	OUTSOLE	PU/PU - slip resistant, antistatic, double density injection
STANDARD	EN ISO 20345:2022 EN ISO 61340-5-1:2016		
UPPER	brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm		



OCCUPATIONAL LOW SHOES ESD
FULL GRAIN LEATHER, NON METALIC



CORSICA

2055

ORDER NO. 2055-01ESD
VERSION 01 01 ESD SR - without composite toe cap and kevlar midsole - antistatic properties **ESD, NON METALIC**
SIZE 36 - 49
STANDARD EN ISO 20347:2022
EN ISO 61340-5-1:2016
UPPER brushed cow suede leather **VELOUR** in a thickness of 1,6 - 1,8 mm

LINING laminated breathable fabric **MESH**
INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic
OUTSOLE **PU/PU** - slip resistant, antistatic, double density injection



WORK & TIGHT



SAFETY LOW SHOES ESD
FULL GRAIN LEATHER, NON METALIC



CORSICA

2045

ORDER NO. 2045-S1PLESD
VERSION S1 PL ESD SR - with composite toe cap and kevlar midsole - antistatic properties **ESD, NON METALIC**
SIZE 36 - 49
STANDARD EN ISO 20345:2022
EN ISO 61340-5-1:2016
UPPER brushed cow suede leather **VELOUR** in a thickness of 1,6 - 1,8 mm

LINING laminated breathable fabric **MESH**
INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic
OUTSOLE **PU/PU** - slip resistant, antistatic, double density injection



OCCUPATIONAL AND SAFETY LOW SHOES ESD
MICROFIBER, NON METALLIC



KORFU


2015

ORDER NO. 2015-02ESD | 2015-S3ESD
VERSION 02 02 FO ESD SRC - without composite toe cap and kevlar midsole, hydrophobic, antistatic properties **ESD, NON METALLIC**
VERSION S3 S3 ESD SRC - with composite toe cap and kevlar midsole, hydrophobic, antistatic properties **ESD, NON METALLIC**
SIZE 02ESD: 35 - 49 | S3ESD: 34 - 50
STANDARD 02: EN ISO 20347:2012 | S3: EN ISO 20345:2011
ESD: EN ISO 61340-5-1:2016
UPPER brushed, breathable poromeric **microfiber** material in combination with textile

LINING laminated breathable fabric **MESH**
INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic
OUTSOLE **PU/PU** - resistant to fuel oils, slip resistant, antistatic, double density injection



DRY SOLE NON METALLIC



OCCUPATIONAL AND SAFETY ANKLE SHOES ESD
MICROFIBER, NON METALLIC



RHODOS

2020

ORDER NO. 2020-02ESD | 2020-S3ESD
VERSION 02 02 FO ESD SRC - without composite toe cap and kevlar midsole, hydrophobic, antistatic properties **ESD, NON METALLIC**
VERSION S3 S3 ESD SRC - with composite toe cap and kevlar midsole, hydrophobic, antistatic properties **ESD, NON METALLIC**
SIZE 02ESD: 35 - 49 | S3ESD: 34 - 50
STANDARD 02: EN ISO 20347:2012 | S3: EN ISO 20345:2011
ESD: EN ISO 61340-5-1:2016
UPPER brushed, breathable poromeric **microfiber** material in combination with textile

LINING laminated breathable fabric **MESH**
INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic
OUTSOLE **PU/PU** - resistant to fuel oils, slip resistant, antistatic, double density injection



DRY SOLE NON METALLIC



SAFETY SANDALS ESD
FULL GRAIN LEATHER, NON METALLIC



MICHIGAN

2145

ORDER NO.	2145-S1PESD	LINING	laminated breathable fabric MESH
VERSION	S1 P ESD SRA - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection
STANDARD	EN ISO 20345:2011 EN ISO 61340-5-1:2016		
UPPER	brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm		



DRY SOLE NON METALLIC



WORK & TIGHT



OCCUPATIONAL AND SAFETY SANDALS ESD
FULL GRAIN LEATHER, NON METALLIC



MEMPHIS

2115

ORDER NO.	2115-01ESD 2115-S1ESD	LINING	laminated breathable fabric MESH
VERSION 01	01 FO ESD SRA - without composite toe cap - antistatic properties ESD, NON METALLIC	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
VERSION S1	S1 ESD SRA - with composite toe cap - antistatic properties ESD, NON METALLIC	OUTSOLE	PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection
SIZE	01ESD: 35 - 48 S1ESD: 34 - 50		
STANDARD	01: EN ISO 20347:2012 S1: EN ISO 20345:2011 ESD: EN ISO 61340-5-1:2016		
UPPER	brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm		



DRY SOLE NON METALLIC



SAFETY LOW SHOES ESD - TEXTILE
POWERED BY BOA® FIT SYSTEM, ULTRALIGHT



PALERMO

2085

ORDER NO. 2085-S1PESD
VERSION S1 P ESD SRC - with composite toe cap and kevlar midsole - antistatic properties **ESD**, powered by **BOA® Fit System**
SIZE 36 - 48
STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016
UPPER knitted, abrasion resistant textile

LINING laminated breathable fabric **MESH**
INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic
OUTSOLE **PU/PU** - resistant to fuel oils, slip resistant, antistatic, double density injection



ULTRALIGHT



SAFETY LOW SHOES ESD - POLYAMIDE FABRIC PUTEK
POWERED BY BOA® FIT SYSTEM, ULTRALIGHT



MINNEAPOLIS

2255

ORDER NO. 2255-S3ESD
VERSION S3 ESD SRC - with composite toe cap and kevlar midsole, antistatic properties **ESD**, hydrophobic, powered by **BOA® Fit System**
SIZE 36 - 48
STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016
UPPER polyamide abrasion resistant fabric **PUTEK**

LINING laminated breathable fabric **MESH**
INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic
OUTSOLE **PU/PU** - resistant to fuel oils, slip resistant, antistatic, double density injection



ULTRALIGHT

SAFETY SANDAL ESD - FULL GRAIN LEATHER
POWERED BY BOA® FIT SYSTEM



MEMPHIS

2115

ORDER NO. 2115-S1PBOA
VERSION S1 P ESD SRA - with composite toe cap and kevlar midsole, antistatic properties ESD, powered by BOA® Fit System
SIZE 35 - 48
STANDARD EN ISO 20345:2011 | EN ISO 61340-5-1:2016
UPPER brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm

LINING laminated breathable fabric MESH
INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
OUTSOLE PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection



WORK & TIGHT



SAFETY SANDAL ESD - FULL GRAIN LEATHER,
POWERED BY BOA® FIT SYSTEM, ULTRALIGHT



BILBAO

2165

ORDER NO. 2165-S1BOA
VERSION S1 ESD SRC - with composite toe cap - antistatic properties ESD, powered by BOA® Fit System
SIZE 36 - 48
STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016
UPPER brushed cow suede leather VELOUR in a thickness of 1,7 - 1,9 mm

LINING laminated breathable fabric MESH
INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
OUTSOLE PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection



ULTRALIGHT

SAFETY SANDALS ESD - FULL GRAIN LEATHER
NON METALLIC, ULTRALIGHT



BILBAO

2165

ORDER NO. 2165-S1ESD

VERSION S1 ESD SRC - with composite toe cap - antistatic properties ESD, NON METALLIC

SIZE 36 - 48

STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016

UPPER brushed cow suede leather VELOUR in a thickness of 1,7 - 1,9 mm

LINING laminated breathable fabric MESH

INNER SOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic

OUTSOLE PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection



SAFETY LOW SHOES ESD
FULL GRAIN LEATHER, NON METALLIC, ULTRALIGHT



BARCELONA

2175

ORDER NO. 2175-S1ESD

VERSION S1 ESD SRC - with composite toe cap - antistatic properties ESD, NON METALLIC

SIZE 36 - 48

STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016

UPPER brushed cow suede leather VELOUR in a thickness of 1,7 - 1,9 mm

LINING laminated breathable fabric MESH

INNER SOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic

OUTSOLE PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection



ULTRALIGHT

SAFETY SANDALS ESD
MICROFIBER, NON METALLIC, ULTRALIGHT



MONTANA

2215

ORDER NO. 2215-S1PESD
VERSION S1 P ESD SRC - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC
SIZE 36 - 49
STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016
UPPER brushed, breathable poromeric microfiber material

LINING laminated breathable fabric MESH
INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
OUTSOLE PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection



DRY SOLE

NON METALLIC



ULTRALIGHT



WORK & TIGHT

SAFETY LOW SHOES ESD
MICROFIBER, NON METALLIC, ULTRALIGHT



CAROLINA

2235

ORDER NO. 2235-S1PESD
VERSION S1 P ESD SRC - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC
SIZE 36 - 49
STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016
UPPER brushed, breathable poromeric microfiber material

LINING laminated breathable fabric MESH
INNER INSOLE HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
OUTSOLE PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection



DRY SOLE

NON METALLIC



ULTRALIGHT

OCCUPATIONAL SANDALS
FULL GRAIN LEATHER



LINZ

3995

ORDER NO.	3995-OB	LINING	without lining
VERSION	OB E SR - without toe cap	INNER INSOLE	anatomically shaped PHYLON
SIZE	36 - 41	OUTSOLE	EVA/RUBBER - glued construction
STANDARD	EN ISO 20347:2012		
UPPER	cowhide leather in a thickness of 1,6 - 1,8 mm		



SAFETY SANDALS ESD
MICROFIBER, NON METALLIC



MONTREAL

2105

ORDER NO.	2105-S1PLESD	LINING	laminated breathable fabric MESH
VERSION	S1 PL FO ESD SR - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, antistatic, slip resistant, double density injection
STANDARD	EN ISO 20345:2022 EN ISO 61340-5-1:2016		
UPPER	poromeric microfiber material in a thickness of 1,6 - 1,8 mm		



SAFETY LOW SHOES ESD
MICROFIBER, NON METALIC



NEWCASTLE

2005

ORDER NO.	2005-S3LESD	LINING	laminated breathable fabric MESH
VERSION	S3L FO ESD SR -with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, antistatic, slip resistant, double density injection
STANDARD	EN ISO 20345:2022 EN ISO 61340-5-1:2016		
UPPER	poromeric microfiber material in a thickness of 1,6 - 1,8 mm		



NEW



WORK & TIGHT

NEW



SAFETY ANKLE SHOES ESD
MICROFIBER, NON METALIC



FULHAM

2010

ORDER NO.	2010-S3LESD	LINING	laminated breathable fabric MESH
VERSION	S3L FO ESD SR - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, antistatic, slip resistant, double density injection
STANDARD	EN ISO 20345:2022 EN ISO 61340-5-1:2016		
UPPER	poromeric microfiber material in a thickness of 1,6 - 1,8 mm		



SAFETY SANDALS ESD
FULL GRAIN LEATHER, NON METALLIC



PARMA

2195

ORDER NO. 2195-S1PESD
VERSION S1 P ESD SRA - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC
SIZE 36 - 48
STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016
UPPER brushed cow suede leather **VELOUR** in a thickness of 1,6 - 1,8 mm

LINING laminated breathable fabric **MESH**
INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic
OUTSOLE **PU/PU** - resistant to fuel oils, slip resistant, antistatic, double density injection



SPACE comfort



anatomic DRY SOLE

NON METALLIC



SAFETY LOW SHOES ESD
FULL GRAIN LEATHER, NON METALLIC



RIMINI

2185

ORDER NO. 2185-S1PESD
VERSION S1 P ESD SRA - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC
SIZE 36 - 48
STANDARD EN ISO 20345:2011
EN ISO 61340-5-1:2016
UPPER brushed cow suede leather **VELOUR** in a thickness of 1,6 - 1,8 mm

LINING laminated breathable fabric **MESH**
INNER INSOLE **HI-POLY** - anatomically shaped, lightweight polyurethane foam coated with fabric **MESH**, antistatic
OUTSOLE **PU/PU** - resistant to fuel oils, slip resistant, antistatic, double density injection



SPACE comfort



anatomic DRY SOLE

NON METALLIC

OCCUPATIONAL LOW SHOES
FULL GRAIN LEATHER



TOKIO

2135

ORDER NO.	2135-01	LINING	laminated breathable fabric MESH
VERSION	01 FO SRA - without toe cap	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection
STANDARD	EN ISO 20347:2012		
UPPER	brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm		



WORK & TIGHT



SAFETY LOW SHOES ESD
FULL GRAIN LEATHER



TOKIO

2125

ORDER NO.	2125-S1ESD	LINING	laminated breathable fabric MESH
VERSION	S1 ESD SRA - with composite toe cap - antistatic properties ESD	INNER INSOLE	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH , antistatic
SIZE	36 - 48	OUTSOLE	PU/PU - resistant to fuel oils, slip resistant, antistatic, double density injection
STANDARD	EN ISO 20345:2011 EN ISO 61340-5-1:2016		
UPPER	brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm		

